# **SPECS**



SUITABLE MICS	Make	Model

AKG C568EB

Audio-Technica AT 4073, BP4073, AT897, AT877

Neumann KMR 81i
Røde NTG-2, NTG-3
Sanken CS-2, CS-3e

Schoeps CMIT 5U, SuperCMIT 2U Sennheiser MKH 416, MKH 60, MKE 600

Shure VP89S

Sony ECM 670, ECM 678

**COMPATIBILITY** Mic Type: Shotgun or rifle microphones

Mic Lengths: 250 mm - 280 mm
Mic Diameters: 19 mm - 25 mm
Max. Weight of Mic: 180 grams
Mic Connector: XLR 3-pin Female
Output Connector: XLR 3-pin Male

### PERFORMANCE Wind Attenuation

Vind Attenuation 50 dB (without Windjammer) >60 dB (with Windjammer)

Measured total power - 10Hz - 20kHz, no weighting,

under real wind conditions

Frequency Response Substantially flat (+0db, -3dB)

Measured differential twin microphone technique, 10Hz - 20kHz

Handling Isolation Typically >10dB

Dependent on microphone type and LF band shaping


Temperature Range Safe operating range: Min. -20°C (-5°F)

Max. 38°C (100°F)

#### **DIMENSIONS**

Overall Length:
Body Length:
Max. Diameter:
Height:
Weight:

470 mm (18.5 inch) 330 mm (13.0 inch) 157 mm ( 6.2 inch) 220 mm ( 8.7 inch) 590 g (20.8 oz)



#### **CABLE** Connectors

Neutrik XLR female 3-pin (NC3FXX-B Gold pin, black casing) Neutrik XLR male 3-pin (NC3MXX-B Gold pin, black casing)

Cable Mogami W2697, Flexible PVC jacket 2.5mm OD x 290 mm

Conductors - twin conductors, 16/0.08 A - 28 AWG

Ultra-soft Silicone sleeve, 5.0 mm OD x 190 mm (from XLR3m)

Fully RoHs Compliant, Pin-1 to shell linked

## CONNECTION

Boom thread Brass, 3/8" UNC female

To suit 3/8"16 UNC male & 3/8" BSW

#### **COUNTRY of ORIGIN**