










ASSEMBLY INSTRUCTION

NC3FXX-HD & NC3MXX-HD | XLR Cable Connector

- A** Slide the rubber sealing (1) and the boot (2) onto the cable.
- B** Prepare cable as shown.
- C** Insert wires into the terminals and solder them.
- D** Put chuck onto the cable.
Attention: Pay attention to the guiding key.
- E** Slide insert and chuck together into the housing.
- F** Turning the bushing onto the connector.
- 
- 
- 
- 
- 
- 

► Rubber sealing assembly see on page 2.



ASSEMBLY OF MALE CONNECTOR




- A** Repeat the steps
- F**
- G** Push the rubber sealing onto the plug.
- **Finish**

ORDER OF ASSEMBLY


NC3FXX-HD



Rubber sealing



bushing



chuck




insert



housing

NC3MXX-HD



NEUTRIK AG
NEUTRIK Zürich AG
NEUTRIK USA Inc.
NEUTRIK (UK) Ltd.

LI
CH
USA
UK

T: +423 / 237 24 24
T: +41 44 / 736 5010
T: +1 732 / 901 9488
T: +44 1983 / 811 441

F: +423 / 232 53 93
F: +41 44 / 736 5011
F: +1 732 / 901 9608
F: +44 1983 / 811 439

NEUTRIK Vertriebs GmbH
NEUTRIK France
NEUTRIK Tokyo Ltd.
NEUTRIK Hong Kong Ltd.

DE/NL/AT/DK
FR
JP
HK

T: +49 8131 / 280 890
T: +33 1 / 4131 6750
T: +81 3 / 3663 4733
T: +852 / 2687 6055

F: +49 8131 / 280 830
F: +33 1 / 4131 0511
F: +81 3 / 3663 4796
F: +852 / 2687 6052

Draft. Nr.: BDA 238 / 3102M1731 | Update: 27.04.2009 | Data subject to change without prior notice. ©2009 NEUTRIK®. ALL RIGHTS RESERVED.