

VPTR-1 Mobile Video Production Trailer



DESCRIPTION

The VPTR-1 is a rack-ready 20 foot x 8.5 foot deluxe professional video and audio production trailer with a generous ceiling height of 6'6". It's a modern fully equipped outside broadcast (OB) vehicle fully air-conditioned and outfitted with heavy duty electrical wiring. The extended 8.5 ft. width provides a true 8 ft. wide interior.

Wired for AC shore power, a full-size 50A 120/240 VAC service panel is pre-installed for your immediate and future electrical requirements.

Featuring a professional all white exterior, the production trailer looks great parked outside or inside an arena, corporate meetings, media tours, sports video production, webcasts, downstreaming, religious programming, or news events. Also provides a low cost portable inside control room for professionals who need a quick and economical solution for broadcast and cable productions close to the TV/ shooting set. Cut/directing can be done in real-time during live transmissions in order to minimize post production costs. Also ideally suited for TV studios and stations with a limited budget.

The interior of the production trailer is fully carpeted and finished in a no-glare medium grey high tech acoustic control fabric on the walls and floor. The cabin is air-conditioned for your comfort, featuring stylish wall and console track lighting with optional LED upgrades available. Outside quartz task lighting is extremely useful when working in remote or dimly-lit locations, and packing up safely when the job is finished.

Five, 6 foot high 19" EIA racks comprise the monitor-equipment wall. A laminated 8 foot wide adjustable console table sits in front of the rack wall for your switcher. Other production features include 3 cable feed-thru hatch doors plus a full audio, video, CAT5 and telco I/O panel outside hatch door featuring Canare and Neutrik connectors for quick and efficient interfacing.

There is a 36" wide passenger door on the curb side of the unit, and a rear swing out door which opens to a 4 foot deep lockable storage room. The storage room also allows complete access to the rear of your rack wall to simplify equipment wiring.

Trailers save you thousands of dollars compared to the cost of motor home models, vans and OB trucks that require costly annual maintenance and never seem to want to start when you need them. Trailers can also be pulled by a wide range of tow vehicles, which can be freed up for other assignments after the production trailer has been placed.


Standard Features

20 Foot x 8.5 Foot
White Aluminum Rivetless Exterior (Colors Available)
Generous 80" Interior Head Room
1 Motorized Roof Vent w/Rain Guard
Finished Laminate Ceiling w/Lighting
8 Ft. Console Table
Dexter Torflex Twin Axles (2x 3500 Lb.)
3,000' Lbs. of Extra Gear Carrying Capacity
Rear Bogey/Skate Wheel "Bottom Out" Protection
Dual Rear Stabilizers

Bright Front Corners - ATP Stoneguard Fully Insulated Walls & Ceiling Grey Industrial Carpeted Walls & Floors 15,000 BTU Roof AC Unit with Heat Strip 36" Lockable Passenger Door 40" Lockable Rear Door 4 Lockable Cable I/O Hatches Premium Radial Tires & Gray Mods Five 19" Racks (37RU Per Rack) Aluminum Pull-Out Steps Exterior Quartz Light Observation Deck Available



SPECIFICATIONS





POWER DISTRIBUTION SYSTEM

MAIN SERVICE PANEL
MASTER CUT-OFF SWITCH
& UTILITY OUTLET

COVER OPEN SHOWING BREAKERS





SAFETY SWITCH




POWER INLET RECEPTACLE LOCATED AT BOTTOM OF SAFETY SWITCH




User Manual

POWER OPTIONS





POWER DISTRIBUTION CENTER / BREAKER LAYOUT






User Manual

SHORE POWER CABLE, 50A 120/240V






CONNECTOR WIRING DETAIL




User Manual


TRAILER HITCH CABLE DETAIL


4-WAY PLUG





7-WAY PLUG





- Page 7 -



REPORTING SAFETY DEFECTS

If you believe that your trailer has a defect that could cause a crash or could cause injury or death you should immediately inform the National Highway Traffic Safety Administration (NHTSA) in addition to notifying Markertek Video Supply.

If NHTSA receives similar complaints, it may open an investigation, and if it finds that a safety defect exists in a group of vehicles, it may order a recall and remedy campaign. However, NHTSA cannot become involved in individual problems between you, your dealer or Markertek Video Supply.

To contact NHTSA, you may either call the Auto Safety Hotline at **1-800-424-9393**, (366-0123 in Washington, DC) or write to:

NHTSA U.S. Department of Transportation 400 7th Street SW, (NSA-11) Washington, DC 20590

You can also obtain other information about motor vehicle safety from Markertek:

Markertek Video Supply 1 Tower Drive Saugerties, NY 12477 (800) 522-2025 www.markertek.com

NOTES







THIS TRAILER HAS REAR STABILIZING LEVELERS WHICH MUST BE DEPLOYED ONCE THE TRAILER IS IN LOCATION.

IT IS VERY IMPORTANT TO LIFT THE STABILIZERS BEFORE MOVING THE TRAILER.



MARKERTEK VIDEO SUPPLY

1 Tower Drive • Box 397 • Saugerties, NY 12477 800-522-2025 • 845-246-3036 • FAX 845-246-1757

E-Mail: sales@markertek.com

www.markertek.com

VPTR-1 Manual Rev. 1a.