



# SPECIFICATIONS

## INPUT

<b>Component</b>	<b>Connectors:</b> 3x RCA for Video (Y, Pb, Pr) 2x RCA for Analog Audio (L, R) 1x RCA for Digital Audio (PCM)
<b>Video Resolution:</b> <b>Video Aspect Ratio:</b>	480i, 720p, & 1080i 4:3 & 16:9
<b>HDMI</b>	<b>Connector:</b> 1x HDMI <b>Video Resolution:</b> 480i, 720p, & 1080i <b>HDCP Encryption:</b> Not supported <b>Audio:</b> Embedded PCM & pass-through Dolby® Digital only
<b>VGA</b>	<b>Connectors:</b> 2x Female VGA (Input + Loop-through Output) <b>Video Resolution:</b> 640x480 @ 60 fps 800x600 @ 60 fps 1024x768 @ 60 fps <b>Audio:</b> 2x RCA for Analog Audio (L, R) 1x RCA for Digital Audio (PCM)
<b>Composite</b>	<b>Connectors:</b> 1x RCA for Video (Y) <b>Video Resolution:</b> 480i <b>Audio:</b> 2x RCA for Analog Audio (L, R) 1x RCA for Digital Audio (PCM)

<b>Encoding Profile</b>	
<b>Video</b>	<b>Output Format:</b> MPEG-2 HD MP@ML; ISO 13818-2 <b>Chroma:</b> 4:2:0 <b>Resolution:</b> 720x480; 1280x720; 1920x1080 <b>Frame rate:</b> 29.97 fps (480i); 29.97 fps (1080i); 59.97 fps (720p) <b>Aspect Ratio:</b> 4:3 & 16:9 <b>GOP Structure:</b> I & P frames (user-selectable) <b>Transport Rate:</b> Variable (user-selectable) <b>Video Bit Rate:</b> Variable (user-selectable) <b>Video Pre-filter:</b> Variable (user-selectable) <b>Intra DC Precision:</b> Variable; 8-11 bit (user-selectable) <b>Color Space:</b> YCbCr and RGB
<b>Audio</b>	<b>Output Format:</b> Dolby® Digital AC-3 <b>Sampling rate:</b> 48 kHz <b>Bit rate:</b> Variable; 96 - 448 Kbps (user-selectable)
<b>Closed Captioning</b>	<b>Component:</b> EIA- 608; 1x RCA (CC) <b>HDMI:</b> EIA- 608; 1x RCA (CC) <b>Composite:</b> EIA- 608

## OUTPUT

<b>QAM</b>	<b>Connector:</b> 1x "F" Female (Rear-panel) <b>Modulation:</b> QAM 16, 32, 64, 128, and 256 <b>Standards:</b> ITU-T J.83; Annex A and B <b>DVB Symbol Rate:</b> Variable; up to 7 MSymbol/sec (MBAud) <b>Frequency Range:</b> 54 to 1002 MHz <b>Tuning:</b> CATV Channel Selectable (Ch. 2 to 158) <b>Channels' Bandwidth:</b> 6 MHz <b>RF Level:</b> +40 dBmV ±1 dB <b>RF Level Adjustment:</b> +32 to +42 dBmV, 1 dB increment <b>Frequency Tolerance:</b> ± 0.5 kHz @ 77 °F (25 °C) <b>Frequency Stability:</b> ± 5 kHz over 32 to 122 °F (0 to 50 °C) <b>Amplitude Flatness:</b> ± 0.25 dB (over 6 MHz channel) <b>Phase Noise:</b> -98 dBc (@ 10 kHz) <b>Spurious:</b> -60 dBc <b>Broadband Noise:</b> -70 dBc (@ +35 dBmV output level, 5.5 MHz bandwidth) <b>Impedance:</b> 75 Ω <b>Spectral Inversion:</b> Auto Recognition <b>Carrier Suppression:</b> 45 dB <b>Return Loss:</b> 14 dB typical <b>Signal-to-Noise Ratio (SNR):</b> 40 dB typical <b>MER:</b> 40 dB typical <b>I/Q Phase Error:</b> Less than 1 degree <b>I/Q Amplitude Imbalance:</b> Less than 1%
<b>ASI</b>	<b>Connectors:</b> 1x BNC (Front-panel) <b>Format:</b> DVB-ASI <b>Standard:</b> ETSI EN 50083-9
<b>IP</b>	<b>Connector:</b> 1x RJ45 (Front-panel) <b>Standard:</b> 10/100Base-T Ethernet <b>UDP/RTP:</b> Supported (user-selectable)

## GENERAL

<b>Dimensions (W x D x H):</b>	5.65 x 12.5 x 1.75 inches (144 x 317.5 x 44.5 mm)
<b>Power:</b>	External Power Supply (Input 115-230VAC / Output 12VDC @ 3 Amp)
<b>Power Dissipation:</b>	18 W
<b>Weight (one module):</b>	1.5 lbs (0.7 kg)
<b>Operating Temperature:</b>	32 to 122 °F (0 to 50 °C)
<b>Storage Temperature:</b>	-13 to 158 °F (-25 to 70 °C)
<b>Operating Humidity:</b>	0 to 95% RH @ 35 °C max, non-condensing
<b>Storage Humidity:</b>	0 to 95% RH @ 35 °C max, non-condensing

## ALARMS/MONITORING/CONTROL

<b>Local Monitoring:</b>	1x Status LED 1x Power LED
<b>Local Control:</b>	1x IP Reset button
<b>Remote Monitoring/Control:</b>	GUI-based menu via standard Web browsers (1x RJ45 front-panel connector; 10/100Base-T, also used for IP output)

## RELATED PRODUCTS

Model	Description
HDE-CSV-QAM	MPEG-2 HD Encoder; 1xComponent/HD-SDI/HDMI/VGA/Composite inputs; 1xQAM+1xASI+1xIP outputs
HDE-2H/2S-QAM	MPEG-2 HD Encoder; 2xHDMI + 2xHD-SDI + 4xComponent inputs; 4xQAM + 4xGigE + 4xASI outputs; EAS compatible; 1RU
HDE-4S-QAM	MPEG-2 HD Encoder; 4xHD-SDI + 4xComponent inputs; 4xQAM + 4xGigE + 4xASI outputs; EAS compatible; 1RU
HD264-2S-IP	H.264 HD Encoder; 2xHD-SDI + 2xHDMI + 2xComponent inputs; 2xIP + 4xASI outputs; 1RU
HDE-ASI	HD/SD Encoder; 1xHD-SDI + 4xSD-SDI + 4xAV inputs; 1xASI output; 2RU
SD10E-QAM	SD Encoder; 10xSD-SDI + 10xAV inputs; 1xQAM output; EAS compatible; 2RU
AV10E-QAM	SD Encoder; 10xAV inputs; 1xQAM + 1xASI outputs; EAS compatible; 2RU