STEARTAN SATA Duplicator Series Blu-ray/DVD/CD

Available in up to 15 Targets

Next Generation Technology

Introducing the newly enhanced Spartan SATA Blu-ray/DVD/CD duplicator. Now you can complete multiple duplication tasks with a single duplicator and keep up with today's digital world, where file size is increasing everyday. Higher resolution photos, sharper and clearer HD video, and countless electronic files can easily be duplicated in minutes. From single target to the industry leading 15 target, the Spartan SATA Blu-ray/DVD/CD Duplicator Series includes multiple features with professional results.

Features

Blu-ray/DVD/CD disc support

Support all popular optical media formats including Blu-ray disc

Dynamic Hard-drive Partitioning (DHP)

Saving HD space by adjusting partition size based on file size

Multi-Language Support

Language is displayed in: English, Spanish, Portuguese or Japanese

Advanced Diagnosis Mode

Troubleshoots and sets adjustment for optimal performance

Dual-level Security

Separate Startup & Setup passwords to prevent unauthorized usage



0

Specifications

Operating Type	Stand-alone (No PC Required)	
Internal interface	SATA	,
Target	Up to 15 Targets	
Language Support	English, Spanish, Portuguese	& Japanese
Maximum Writing Speed (Up To) (Actual write speed depends upon media and drive specifications)	BD-R DL:12XDVIBD-RE SL:12XDVIBD-RE DL:12XDVI	D+RW: 8X D-R: 24X D-RW: 8X D+R: 24X -RW: 52X -R: 52X
Supported Disc Formats	BD ROM, BD-R, BD-R DL, BD-F DVD ROM, DVD-R, DVD-RW, I DVD+RW, CD-DA, CD ROM, C Multi-session Photo CD [™] , CD CD ROM XA, & CD Extra (CD F	DVD+R, D-R, CD-RW, D-I, Video CD,
	*6	

Supported Recording Discs	12cm 25GB BD-R, 12cm 25GB BD-RE, 12cm 50GB BD-R DL, 12cm 50GB BD-RE DL, 12cm 4.7GB DVD-R/RW, 12cm 4.7GB DVD+R/RW, 12cm 8.5GB DVD+R DL, 12cm 8.5GB DVD-R DL, 12cm 80min/700MB CD-R, 12cm 74min/650MB CD-RW, 8cm 1.47GB mini DVD-R, 8cm 24min/210MB mini CD-R, 8cm 50MB Business Card CD-R	
Built-in Hard Drive(optional)	Supports up to 1TB HDD	
External PC Link	USB 2.0	
Power Adapter	Input: 100 ~ 240V AC Output: +5V DC, 3.8A	
Operating Temperature	40°F ~ 95°F	
Operating Humidity	20% ~ 90%	
Regulations	FCC, CE, UL, RoHS	

Specifications are subject to change without notice.





THE TOTAL DUPLICATION SOLUTION PROVIDER

1-888 PICK-ILY (742-5459) www.ily.com