

Wireless Presenters with Wireless Speakers Your Audience Will Hear Loud and Clear



Quick Look:

Audience Size: 3,000
 Room Size: 25,000 sq. ft.
 SPL 104 dB
 CE Listing
 Jensen Speakers
 Amplivox Wireless Mics
 Lightweight and Portable
 Multimedia Cables Included
 Made in USA
 6 Year Warranty



Complete Wireless Presentation System
 for Audiences up to 3,000.

No dangerous, unsightly cables or wires
 that clutter the space.

Wireless Voice Projector & Wireless
 Speaker require POWER

10 D-cell Alkaline Batteries for up to 200
 hours or S1460 International AC Adapter/
 Recharger or S1465 NiCad Rechargeable
 Battery Pack

(All Sold Separately)

**Place the wireless powered
 speaker where you need it -
 within 300 feet of the
 Wireless Voice Projector.**

WHAT'S IN THE BOX:

SW225 Wireless Voice
 Projector with S1204-70
 Wireless Powered Speaker
 with built in receiver; 2
 Tripods & Carrying Case on
 Wheels; Multimedia Cables;
 Lapel & Headset
 Mics with transmitter



SW227 WIRELESS POWERED SPEAKER VOICE PROJECTOR KIT - Includes SW225 Wireless Voice Projector with S1204-70 Wireless Powered Dual Module Speaker & Transmitter, Two S1090 tripods. Rugged nylon reinforced carrying case on wheels with luggage handle (S1960) and computer interface cables.

INTERNATIONAL AC ADAPTER/RECHARGER - 110/240 volt, 50/60Hz. 15-volt center positive, 2 amps, 7.5-ft cord. For S805A/SW805A amplifiers only.

NICAD BATTERY PACK - Heavy duty rechargeable; for S805A/SW805A amps - requires S1460 AC Adapter/Recharger.

Model #	Shpg. Weight	MSRP
SW227	45 lbs.	1,496.00
S1460	2 lbs.	131.00
S1465	4 lbs.	200.00

650 Anthony Trail, Suite D., Northbrook, IL 60062

Made in the U.S.A. Limited 6 year Warranty

Wireless Voice Projector SW225

Features & Specs

Amplifier Exclusive built-in 50-watt multimedia stereo amplifier SW805A.

Power Controls On-off switch with LED power indicator light. Jack for optional, external AC adapter/recharger.

Power Source 110/240V AC Adapter/recharger available (S1460). 10 D-cell Alkaline batteries (not included) for up to 200 hrs. Sold Separately.

Auxiliary Input Auxiliary input with separate volume and tone controls for a Computer Projector, CD or tape player. Capture your audience's attention with a mixed media presentation by adding music. Audio Cables for laptop or projector included.

Line Out Jack You can record your presentation as it is happening.

Microphone Model S2030A. Professional low-impedance, cardioid pattern, dynamic microphone, steel case, frequency response 50-15,000 Hz; with 15-ft. cable. Wireless Audio Technica lapel mic with transmitter and on-off switch.

Microphone Jacks 1 each dynamic, condenser with phantom power and wireless. Microphone volume control adjusts all mics together. All 3 mic inputs and auxiliary input can be used at the same time.

Dual Wireless Capability Two presenters can be wireless with purchase of additional wireless mic kit.



Back of SW225: amplifier control panel

Speakers Two 6-in. x 8-in. Jensen design oval speakers

Speaker Jacks 2 jacks; 1 per line input channel. Each jack can drive 4- or 8-ohm speakers. Mic inputs are added equally to left and right channels. Output driver is placed into standby mode when its output jack is empty, reducing power drain and prolonging battery life.

Construction Carpeted cabinet with built-in tripod mount and pocket handle.

Dimensions 14-in. x 10-in. x 6.5-in.

Easy to Use! Just plug and speak!

Quick Look:

Audience Size: 1,500
Room Size: 15,000 sq. ft.
SPL 104 dB
CE Listing
Jensen Speakers
Amplivox Wireless Mics
Lightweight and Portable
Multimedia Cables Included
Made in USA
6 Year Warranty



Add the SW225 to a non-sound lectern to reach 1,500 people!

What's In the Box?

SW225 Voice Projector
Wireless Lapel & Headset
Mics with Transmitter
Multimedia Cables



SW225 WIRELESS VOICE PROJECTOR - Two 6-in. x 8-in. speakers, SW805A 50-watt multimedia stereo amplifier with built-in wireless receiver built into carpeted cabinet with tripod mount, WIRELESS HEADSET & LAPEL MICS & transmitter (14-in.x10-in. x 6½-in.); Includes computer and stereo interface cables.

INTERNATIONAL AC ADAPTER/RECHARGER - 110/240 volt, 50/60Hz. 15-volt center positive, 2 amps, 7.5-ft cord. For S805A/SW805A amplifiers only.

NICAD BATTERY PACK - Heavy duty rechargeable; for S805A/SW805A amps - requires S1460 AC Adapter/Recharger.

Model #	Shpg. Weight	MSRP
SW225	17 lbs.	881.00
S1460	2 lbs.	131.00
S1465	4 lbs.	200.00