

# AT8010 OMIDIRECTIONAL CONDENSER MICROPHONE



- All-purpose condenser microphone ideal for handheld interviews and general audio acquisition
- Omni pattern provides maximum ambient pickup
- Switchable 80 Hz high-pass filter minimizes pickup of undesired low-frequency sounds
- Operates on battery or phantom power

The AT8010 requires 11V to 52V DC phantom power *or* a 1.5V AA battery for operation. A battery need not be in place for phantom power operation.

**Battery installation:** Unscrew the lower section of the microphone body, just below the nameplate. Insert a fresh 1.5V AA battery in the handle compartment ("+" end up), then reassemble the microphone. Alkaline batteries are recommended for longest life. Remove the battery during long-term storage.

Output from the microphone's XLRM-type connector is low impedance (Lo-Z) balanced. The signal appears across Pins 2 and 3; Pin 1 is ground (shield). Output phase is "Pin 2 hot" – positive acoustic pressure produces positive voltage at Pin 2.

To avoid phase cancellation and poor sound, all mic cables must be wired consistently: Pin 1-to-Pin 1, etc.

An integral 80 Hz high-pass filter provides easy switching from a flat frequency response to a low-end roll-off. The roll-off position reduces the pickup of low-frequency ambient noise (such as traffic, air-handling systems, etc.), room reverberation and mechanically coupled vibrations.

The high sensitivity of the AT8010 assures useful output and an excellent match to most input sources. In some cases, however, an attenuator such as the Audio-Technica AT8202 may be required between the microphone and preamplifier to avoid overloading sensitive input stages.

The microphone is RoHS compliant—free from all substances specified in the EU directive on hazardous substances.

Avoid leaving the microphone in the open sun or in areas where temperatures exceed 110° F (43° C) for extended periods. Extremely high humidity should also be avoided.

## AT8010 SPECIFICATIONS†


<b>ELEMENT</b>	Fixed-charge back plate permanently polarized condenser
<b>POLAR PATTERN</b>	Omnidirectional
<b>FREQUENCY RESPONSE</b>	20-20,000 Hz
<b>LOW FREQUENCY ROLL-OFF</b>	80 Hz, 12 dB/Octave
<b>OPEN CIRCUIT SENSITIVITY</b> (Phantom / Battery)	−44 dB (6.3 mV) / −45 dB (5.6 mV) re 1V at 1 Pa*
<b>IMPEDANCE</b> (Phantom / Battery)	250 ohms / 300 ohms
<b>MAXIMUM INPUT SOUND LEVEL</b> (Phantom / Battery)	137 dB / 123 dB SPL, 1 kHz at 1% T.H.D.
<b>DYNAMIC RANGE</b> (typical) (Phantom / Battery)	113 dB / 99 dB, 1 kHz at Max SPL
<b>SIGNAL-TO-NOISE RATIO¹</b>	70 dB, 1 kHz at 1 Pa*
<b>PHANTOM POWER REQUIREMENTS</b>	11-52V DC, 2 mA typical
<b>BATTERY TYPE</b>	1.5V AA/UM3
<b>BATTERY CURRENT / LIFE</b>	0.4 mA / 1200 hours typical (alkaline)
<b>SWITCH</b>	Flat, roll-off
<b>WEIGHT</b> (less accessories)	165 g (5.8 oz)
<b>DIMENSIONS</b>	178.0 mm (7.01") long, 26.0 mm (1.02") head diameter
<b>OUTPUT CONNECTOR</b>	Integral 3-pin XLRM-type
<b>ACCESSORIES FURNISHED</b>	AT8405a stand clamp for 5/8"-27 threaded stands; 5/8"-27 to 3/8"-16 threaded adapter; AT8136 windscreen; battery; soft protective pouch

†In the interest of standards development, A.T.U.S. offers full details on its test methods to other industry professionals on request.

\*1 Pascal = 10 dynes/cm² = 10 microbars = 94 dB SPL

¹ Typical, A-weighted, using Audio Precision System One.

Specifications are subject to change without notice.



Audio-Technica U.S., Inc., 1221 Commerce Drive, Stow, Ohio 44224

Audio-Technica Limited, Old Lane, Leeds LS11 8AG England

www.audio-technica.com

P51968 ©2007 Audio-Technica U.S., Inc. Printed in Japan

