

OPERATING PRECAUTIONS

Battery Charger

- It is not abnormal for the recharger and the rechargable batteries to become warm during recharging.

Batteries

- For best performance and optimal safety, use only the included 2000 mAh Ni-MH or similar type batteries.
- It is often necessary to cycle new or deeply discharged Ni-MH batteries two or three times before they reach peak performance. To cycle the batteries, simply use them as you normally would and then recharge them.

COMPLIANCE WITH FCC RULES (USA ONLY)

This device complies with Part 15 of FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC WARNING

You are cautioned that any changes or modifications not expressly approved in this manual could void your authority to operate this equipment.

NOTICE

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

DANGER

This charger is designed only for Ni-MH rechargable batteries. To avoid personal injury and damage, do not attempt to charge alkaline batteries or any other rechargable batteries besides Ni-MH.

WARNING

- To prevent fire or shock hazard, do not expose this product to drips or splashes.
- To prevent fire, do not place any naked flame sources (such as lighted candles) on the product.
- To prevent fire, do not cover the ventilation of product with newspaper, tablecloths, curtains, etc.
- Do not install this product in a confined space such as a bookcase or similar unit.
- Do not open the cover. No user serviceable parts inside.
- Do not place any objects filled with liquids, such as vases, on the product.

CAUTION

- Do not use the charger in extremely cold or hot conditions.
- Keep the charger out of reach of small children.
- Danger of explosion if the wrong type of batteries are used.
- The battery rating label is on the bottom of the apparatus.
- Replace batteries only with the same or equivalent type.
- The charger should be located close enough to the AC outlet so that you can easily grasp the AC adapter at anytime. In case of emergency, disconnect the AC adapter quickly.
- Do not expose batteries or charger to excessive heat such as direct sunlight, fire or the like.

RECYCLING OF NI-MH BATTERIES

- Do not dispose the batteries as unsorted municipal waste; use separate collection facilities.
- Contact your local government for information regarding the collection systems available.

CANADA ONLY

This Class B digital apparatus complies with Canadian ICES-003. Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.

ATW-CHG2

Two-Bay Recharging Station

To reduce the environmental impact of a multi-language printed document, product information is available online at www.audio-technica.com in a selection of languages.

Afin de réduire l'impact sur l'environnement de l'impression de plusieurs langues, les informations concernant les produits sont disponibles sur le site www.audio-technica.com dans une large sélection de langue.

Para reducir el impacto al medioambiente, y reducir la producción de documentos en varios leguajes, información de nuestros productos están disponibles en nuestra página del Internet: www.audio-technica.com.

Para reduzir o impacto ecológico de um documento impresso de várias línguas, a Audio-Technica providência as informações dos seus produtos em diversas línguas na www.audio-technica.com.

Per evitare l'impatto ambientale che la stampa di questo documento determinerebbe, le informazioni sui prodotti sono disponibili online in diverse lingue sul sito www.audio-technica.com.

Der Umwelt zuliebe finden Sie die Produktinformationen in deutscher Sprache und weiteren Sprachen auf unserer Homepage: www.audio-technica.com.

Om de gevolgen van een gedrukte meertalige handleiding op het milieu te verkleinen, is productinformatie in verschillende talen "on-line" beschikbaar op: www.audio-technica.com.

本公司基於減少對環境的影響，將不作多語言文件的印刷，有關產品訊息可在 www.audio-technica.com 的官方網頁上選擇所屬語言及瀏覽。

本公司基于减少对环境的影响，将不作多语言文档的印刷，有关产品信息可在 www.audio-technica.com 的官方网页上选择所属语言和浏览。

자원절약, 환경보호를 위해 국문 사용 설명서는 인쇄하지 않았습니다. 제품정보는 www.audio-technica.com 에서 원하는 언어 선택 후에 다운로드 받으실 수 있습니다.

For use with 2000 Series wireless transmitters:

- ATW-T210a UniPak® Transmitter
- ATW-T220a Handheld Transmitter



ATW-CHG2 Features

- Batteries are charged within the transmitters.
- Versatile unit charges ATW-T220a handheld transmitters and/or ATW-T210a UniPak® transmitters (in any combination).
- Built-in safety feature monitors cell voltage and automatically turns off the unit if problems are detected.
- Automatic shut-off if alkaline (non-rechargeable) batteries are installed.
- Automatic shut-off if damaged batteries are installed.
- Maintenance charging prevents battery self-discharge until the transmitter is removed from charger.
- Includes Ni-MH rechargeable batteries – 2 x AA 2000 mAh

LED Status Indication

Charger indicator status	Charging status	Transmitter status
Off	Power off	Transmitter not in unit
Red light	Charging*	Transmitter in unit
Red flashing	Charging error (Charging is stopped)	Transmitter in unit
Off	Charging is finished (Still maintenance charging)	Transmitter in unit

Note: Red flashing light (charging error) is caused by use of alkaline (non-rechargeable) or damaged battery.

***Note: If a transmitter with fully charged batteries is placed in the charger, the red light will remain on for a minimum of 3 hours, even though the batteries are fully charged.**

How to charge

1. Connect the power cord.
2. Set the transmitter's power switch to the off position.
(Note: The transmitter's power is automatically turned off if the transmitter is set in the charger with its power switch on; in this case, the transmitter will resume operation when it is removed from the charger.)
3. Install the Ni-MH AA batteries in the transmitter, observing correct polarity as marked inside the transmitter. For installation instructions, see the 2000 Series installation & operation manual.
4. Insert the transmitter into the charger with transmitter charging contacts facing toward the charger's contact pins.
5. Power is supplied to the charging bay when the transmitter is set into the unit; at this point the red indicator of each port lights.
(Note: If the red indicator does not light, poor contact may be the cause; set the transmitter in the charger again.)
6. When the charge is completed, the red indicator is turned off.
(Note: Maximum charging time is about ten hours.)
7. The unit keeps charging with ultra-low current (maintenance charge) until the transmitter is removed from the charger.

Specifications*

Input Rating	12V DC, 230 mA (maximum)
Output Rating	3.2V DC, 230 mA x2
Charging Time	Approx. 10 hours (2000 mAh Ni-MH)
Operating Temperature	0~+40° C
Dimensions	Approx. 131.0 mm (5.16") W x 130.0 mm (5.12") D x 105.0 mm (4.13") H
Weight	Approx. 40 g (1.4 oz)

*Specifications are subject to change without notice.