

HEADPHONES HPS3000

Technical Specifications

Version 1.1 August 2006

ENGLISH



www.behringer.com



HEADPHONES HPS3000

HIGH-PERFORMANCE STUDIO HEADPHONES

- ▲ Ultra-wide frequency response
- ▲ High-definition bass and super-transparent highs
- ▲ Ultra-wide dynamic range
- ▲ High-efficiency cobalt capsule
- ▲ 1/8" connector plus 1/4" adapter included
- ▲ Single-sided cord with oxygen-free copper wires
- ▲ Optimized oval-shaped ear cups
- ▲ Ultra-rugged headband construction
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

SPECIFICATIONS

Capsule diameter	40 mm
Frequency response	20 Hz - 20 kHz
Max. power handling	100 mW
Impedance	64 Ohm
Sensitivity	110 dB @ 1 kHz
Cord length	2.0 m
Connector	1/8" TRS connector plus 1/4" TRS adapter

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. The names of companies, institutions or publications pictured or mentioned and their respective logos are registered trademarks of their respective owners. Their use neither constitutes a claim of the trademarks by BEHRINGER nor affiliation of the trademark owners with BEHRINGER. BEHRINGER accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colours and specification may vary slightly from product. Products are sold through our authorised dealers only. Distributors and dealers are not agents of BEHRINGER and have absolutely no authority to bind BEHRINGER by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER International GmbH. BEHRINGER® is a registered trademark.

ALL RIGHTS RESERVED. © 2006 BEHRINGER International GmbH,
Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany.
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903