

For more Information  
please call

1-800-Belden1



## General Description:

24 AWG stranded (7x32) tinned copper conductors, Datalene® insulation, dual twisted pairs, overall Beldfoil® shield (100% coverage), 24 AWG drain wire, PVC jacket in Zip-Cord construction.

## Physical Characteristics (Overall)

### Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
2	24	7x32	TC - Tinned Copper	.024

Total Number of Conductors: 4

### Insulation

Insulation Material:

Insulation Trade Name	Insulation Material
Datalene®	FHDPE - Foam High Density Polyethylene

### Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Bonded Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
24

Inner Shield Drain Wire Stranding: 7x32

Inner Shield Drain Wire Diameter: .024

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

### Overall Cable

Overall Nominal Diameter: 0.180 x 0.360 in.

### Pair

Pair Color Code Chart:

Number	Color
1	Red & Black
2	Red & Black

## Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +60°C

UL Temperature Rating: 60°C

Bulk Cable Weight: 33 lbs/1000 ft.

Max. Recommended Pulling Tension: 33 lbs.

Min. Bend Radius/Minor Axis: 2 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMR

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Other Specification:	AES/EBU

**Flame Test**

UL Flame Test:	UL1666 Vertical Shaft
CSA Flame Test:	FT4

**Plenum/Non-Plenum**

Plenum (Y/N):	No
---------------	----

**Electrical Characteristics (Overall)**

**Nom. Characteristic Impedance:**

**Impedance (Ohm)**  
110

**Nom. Inductance:**

**Inductance (µH/ft)**  
.18

**Nom. Capacitance Conductor to Conductor:**

**Capacitance (pF/ft)**  
12

**Nom. Capacitance Cond. to Other Conductor & Shield:**

**Capacitance (pF/ft)**  
26

**Nominal Velocity of Propagation:**

**VP (%)**  
76

**Nom. Conductor DC Resistance:**

**DCR @ 20°C (Ohm/1000 ft)**  
23.7

**Nom. Attenuation:**

Freq. (MHz)	Attenuation (dB/100 ft.)
0.384	0.290
0.706	0.710
0.768	0.770
1.024	0.940
1.411	1.100
1.536	1.100
2.048	1.300
2.822	1.400
3.072	1.400
4.096	1.500
5.645	1.700
6.144	1.800
8.192	2.000
11.290	2.200
12.288	2.300
24.576	3.100

**Max. Operating Voltage - UL:**

**Voltage**  
300 V RMS

**Max. Recommended Current:**

**Current**  
2.75 Amps per conductor @ 25°C

**Notes (Overall)**

**Notes:** For cross-connect use with 1803F (et al.) Digital Audio Snake Cables. The jacket and shield are bonded so both can be removed on automatic stripping equipment.

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1802B Z4BN1000	1,000 FT	37.000 LB	VIO Z4B		2 #24 FHDPE PR FS PVC PARA
1802B Z4BU1000	1,000 FT	35.000 LB	VIO Z4B		2 #24 FHDPE PR FS PVC PARA
1802B Z4B1000	1,000 FT	37.000 LB	VIO Z4B	C	2 #24 FHDPE PR FS PVC PARA
1802B Z4B500	500 FT	18.500 LB	VIO Z4B	C	2 #24 FHDPE PR FS PVC PARA
1802B 010N1000	1,000 FT	37.000 LB	BLACK		2 #24 FHDPE PR FS PVC PARA

**Notes:**  
C = CRATE REEL PUT-UP.

Revision Number: 3    Revision Date: 03-17-2014

© 2017 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).