

## 7987P Multi-Conductor - 4-Pair UTP Cable for RGB Video



For more Information  
please call

1-800-Belden1



### General Description:

NanoSkew™ 24 AWG twisted pairs solid bare copper conductors, FEP insulation, rip cord, Flamarrest® jacket.

### Usage (Overall)

Suitable Applications: UTP Based Video Applications, Not for data transmission requiring TIA/EIA Category qualifications, RGB

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
4	24	Solid	BC - Bare Copper

Total Number of Conductors: 8

#### Insulation

Insulation Material:

Insulation Material
FEP - Fluorinated Ethylene Propylene

#### Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Outer Jacket Ripcord: Yes

#### Overall Cable

Overall Nominal Diameter: 0.201 in.

#### Pair

Pair Color Code Chart:

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

Bulk Cable Weight: 21 lbs/1000 ft.

Max. Recommended Pulling Tension: 40 lbs.

Min. Bend Radius/Minor Axis: 0.200 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

## 7987P Multi-Conductor - 4-Pair UTP Cable for RGB Video

EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

### Flame Test

UL Flame Test:	NFPA 262
CSA Flame Test:	FT6

### Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	7987R

### Electrical Characteristics (Overall)

#### Nom. Characteristic Impedance:

Impedance (Ohm)  
100

#### Nominal Velocity of Propagation:

VP (%)  
70

#### Typical Delay Skew:

Delay Skew (ns/ft)  
0.007

#### Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)  
9

#### Max. Operating Voltage - UL:

Voltage  
300 V RMS

### Electrical Characteristics-Premise (Overall)

#### Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance
1	100 ± 15	100 ± 15
4	100 ± 15	100 ± 15
8	100 ± 15	100 ± 15
10	100 ± 15	100 ± 15
16	100 ± 15	100 ± 15
20	100 ± 15	100 ± 15
25	100 ± 15	100 ± 15
31.25	100 ± 15	100 ± 15
62.5	100 ± 15	100 ± 15
100	100 ± 15	100 ± 15

### Notes (Overall)

Notes: Jacket sequentially marked at 2 ft. intervals.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
7987P 1NDU1000	1,000 FT	22.000 LB	MAROON 1ND		4 PR #24 FEP FLRST
7987P 1NDU1640	1,640 FT	36.080 LB	MAROON 1ND		4 PR #24 FEP FLRST

Revision Number: 3 Revision Date: 08-01-2013

© 2016 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).



7987P Multi-Conductor - 4-Pair UTP Cable for RGB Video