

For more Information  
please call

1-800-Belden1



### General Description:

22 AWG stranded (7x29) .031" bare compacted copper conductor, polyethylene insulation, tinned copper/bare copper double braid shield (95% coverage), PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	22	7x29	BCC - Bare Compacted Copper	.031

Total Number of Conductors: 1

#### Insulation

Insulation Material:

Insulation Material	Dia. (in.)
PE - Polyethylene	.193

#### Outer Shield

Outer Shield Material:

Layer #	Type	Outer Shield Material	Coverage (%)
1	Braid	TC - Tinned Copper	95.000
2	Braid	TC - Tinned Copper	95.000

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

Overall Nominal Diameter: 0.304 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +60°C

Non-UL Temperature Rating: 60°C

Bulk Cable Weight: 63 lbs/1000 ft.

Max. Recommended Pulling Tension: 108 lbs.

Min. Bend Radius/Minor Axis: 3 in.

Min. Flexing Radius: 4.500 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: No

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

RG Type: 59/U

#### Suitability

Suitability - Indoor: Yes

**Plenum/Non-Plenum**

Plenum (Y/N): No

**Electrical Characteristics (Overall)**

**Nom. Characteristic Impedance:**

Impedance (Ohm)  
75

**Nom. Inductance:**

Inductance (µH/ft)  
0.118

**Nom. Capacitance Conductor to Shield:**

Capacitance (pF/ft)  
21

**Nominal Velocity of Propagation:**

VP (%)  
66

**Nominal Delay:**

Delay (ns/ft)  
1.54

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)  
12.2

**Nominal Outer Shield DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)  
1.7

**Nom. Attenuation:**

Freq. (MHz)	Attenuation (dB/100 ft.)
1	.3
3.6	.5
10.0	.9
71.5	2.5
135	3.6
270	5.1
360	6.0
540	7.4
720	8.7
750	8.9
1000	10.5

**Max. Operating Voltage - Non-UL:**

Voltage  
2900 V RMS

**Other Electrical Characteristic 1:** Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination.

**Other Electrical Characteristic 2:** Return Loss tested in accordance with ASTM D-4566 paragraph 45.3, using a 75 Ohm fixed bridge and termination.

**Minimum Structural Return Loss:**

Start Freq. (MHz)	Stop Freq. (MHz)	Min. SRL (dB)
5	216	27
217	830	23

**Sweep Test**

**Sweep Testing:** 100% sweep tested. 5 MHz to 850 MHz.

**Notes (Overall)**

**Notes:** Compacted copper combines the Impedance uniformity of solid conductors and the "nick-resistance" of stranded conductors.

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8281F G7V1000	1,000 FT	65.000 LB	RED, MATTE	C	#21H PE DBLB PVC
8281F G7W1000	1,000 FT	65.000 LB	GREEN, MATTE	C	#21H PE DBLB PVC
8281F G7X1000	1,000 FT	65.000 LB	BLUE, MATTE	C	#21H PE DBLB PVC
8281F J5C1000	1,000 FT	65.000 LB	BLACK, VIVID MATTE	C	#21H PE DBLB PVC
8281F J5C500	500 FT	35.000 LB	BLACK, VIVID MATTE		#21H PE DBLB PVC

# Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

## 8281F Coax - Double Braided RG-59/U Type

8281F U901000	1,000 FT	65.000 LB	GRAY, MATTE	C	#21H PE DBLB PVC
---------------	----------	-----------	-------------	---	------------------

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 04-30-2013

© 2017 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.  
Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.  
All sales of Belden products are subject to Belden's standard terms and conditions of sale.  
Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.