

For more Information  
please call

1-800-Belden1



## General Description:

20 AWG stranded (7x28) .038" tinned copper conductors, polyethylene insulation, Beldfoil® (100% coverage) plus a tinned copper braid shield (55% coverage), sunlight-resistant PVC jacket.

## Physical Characteristics (Overall)

### Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1	20	7x28	TC - Tinned Copper	0.038

Total Number of Conductors: 2

### Insulation

Insulation Material:

Insulation Material	Dia. (in.)
PE - Polyethylene	0.078

### Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	55

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
20	7x28H	TC - Tinned Copper

### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

### Overall Cable

Overall Nominal Diameter: 0.238 in.

### Pair

Pair Color Code Chart:

Number	Color
1	Clear & Blue

Pair Lay Length & Direction:

Twists (twist/ft)
2.750

## Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +80°C

UL Temperature Rating: 80°C (UL AWM Style 2464)

Bulk Cable Weight: 36 lbs/1000 ft.

Max. Recommended Pulling Tension: 48 lbs.

Min. Bend Radius/Minor Axis: 2.400 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CL2, CM

CEC/C(UL) Specification: CM

AWM Specification: UL Style 2464 (300 V 80°C)

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
PMSHA Specification:	P-7K-SC-182141
Customer Part Number Reference Specification:	Allen Bradley P/N 1770-CD

**Flame Test**

UL Flame Test:	UL1685 UL Loading
----------------	-------------------

**Suitability**

Sunlight Resistance:	Yes
----------------------	-----

**Plenum/Non-Plenum**

Plenum Number:	89463
----------------	-------

**Electrical Characteristics (Overall)**

**Nom. Characteristic Impedance:**

Impedance (Ohm)

78

**Nom. Inductance:**

Inductance (µH/ft)

0.12

**Nom. Capacitance Conductor to Conductor:**

Capacitance (pF/ft)

19.7

**Nom. Capacitance Cond. to Other Conductor & Shield:**

Capacitance (pF/ft)

36

**Nominal Velocity of Propagation:**

VP (%)

66

**Nominal Delay:**

Delay (ns/ft)

1.54

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)

9.5

**Nominal Outer Shield DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)

4.1

**Nom. Attenuation:**

Freq. (MHz)	Attenuation (dB/100 ft.)
1	0.6
10	2.1
50	5.0
100	7.5
200	11.0
400	16.0

**Max. Operating Voltage - UL:**

Voltage
300 V RMS (UL AWM Style 2464)
300 V RMS (NEC Type CM)
300 V RMS (NEC Type CL2)

Other Electrical Characteristic 1:

DC Resistance Unbalanced: .77 Ohms/1000 ft Max

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

9463 J22U1000	1,000 FT	38.000 LB	BLUE, STRONG		78 OHM TWINAX
9463 J22U500	500 FT	19.500 LB	BLUE, STRONG		78 OHM TWINAX
9463 J22100	100 FT	4.400 LB	BLUE, STRONG		78 OHM TWINAX
9463 J221000	1,000 FT	39.000 LB	BLUE, STRONG	C	78 OHM TWINAX
9463 J2212000	12,000 FT	492.000 LB	BLUE, STRONG	C Y	78 OHM TWINAX
9463 J22500	500 FT	19.500 LB	BLUE, STRONG		78 OHM TWINAX
9463 J226000	6,000 FT	234.000 LB	BLUE, STRONG	C Z	78 OHM TWINAX
9463 0011000	1,000 FT	39.000 LB	BROWN		78 OHM TWINAX
9463 00110000	10,000 FT	380.000 LB	BROWN	C Z	78 OHM TWINAX
9463 00112000	12,000 FT	492.000 LB	BROWN	C Y	78 OHM TWINAX
9463 0016000	6,000 FT	234.000 LB	BROWN	C Z	78 OHM TWINAX
9463 0031000	1,000 FT	39.000 LB	ORANGE	C	78 OHM TWINAX
9463 00310000	10,000 FT	380.000 LB	ORANGE	C Z	78 OHM TWINAX
9463 00312000	12,000 FT	492.000 LB	ORANGE	C Y	78 OHM TWINAX
9463 0036000	6,000 FT	234.000 LB	ORANGE	C Z	78 OHM TWINAX
9463 0071000	1,000 FT	39.000 LB	VIOLET	C	00 OHM TWINAX
9463 0076000	6,000 FT	234.000 LB	VIOLET	C Z	78 OHM TWINAX

**Notes:**

C = CRATE REEL PUT-UP.

Y = FINAL PUT-UP LENGTH MAY VARY -10% TO +20% FROM LENGTH SHOWN.MAY CONTAIN 2 PIECES. MINIMUM LENGTH OF ANY ONE PIECE IS 1500'.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 3    Revision Date: 08-01-2013

© 2017 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).