



For more Information
please call

1-800-Belden1



General Description:

24 AWG stranded (7x32) TC conductor, polyolefin insulation, individually shielded Beldfoil® (100% coverage) numbered/color-coded PVC jackets, jackets and shields bonded to strip simultaneously, overall Beldfoil shield and 24 AWG TC drain wire.

Physical Characteristics (Overall)

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material | Dia. (in.) |
|---------|-----|-----------|--------------------|------------|
| 2 | 24 | 7x32 | TC - Tinned Copper | .024 |

Total Number of Conductors: 4

Insulation

Insulation Material:

| Insulation Material | Dia. (in.) |
|---------------------|------------|
| PO - Polyolefin | 0.040 |

Inner Shield

Inner Shield Material:

| Inner Shield Trade Name | Type | Inner Shield Material | Coverage (%) |
|-------------------------|------|------------------------------|--------------|
| Beldfoil® | Tape | Aluminum Foil-Polyester Tape | 100 |

Inner Shield Drain Wire AWG:

| AWG |
|-----|
| 24 |

Inner Shield Drain Wire Stranding: 7x32

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

Inner Jacket

Inner Jacket Material:

| Inner Jacket Material | Nom. Dia. (in.) |
|--------------------------|-----------------|
| PVC - Polyvinyl Chloride | 0.111 |

Inner Jacket Color Code Chart:

| Number | Color |
|--------|-------|
| 1 | Brown |
| 2 | Red |

Outer Shield

Outer Shield Material:

| Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|-------------------------|------|------------------------------|--------------|
| Beldfoil® | Tape | Aluminum Foil-Polyester Tape | 100 |

Outer Shield Drain Wire AWG:

| AWG | Stranding | Drain Wire Conductor Material |
|-----|-----------|-------------------------------|
| 24 | 7x32 | TC - Tinned Copper |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|--------------------------|
| PVC - Polyvinyl Chloride |

Outer Jacket Ripcord: Yes

Overall Cable

Overall Nominal Diameter: 0.301 in.

Pair

Pair Color Code Chart:

| Color |
|-------------|
| Red & Black |

Mechanical Characteristics (Overall)

| | |
|-----------------------------------|-----------------|
| Operating Temperature Range: | -35°C To +75°C |
| Bulk Cable Weight: | 42 lbs/1000 ft. |
| Max. Recommended Pulling Tension: | 55.400 lbs. |
| Min. Bend Radius/Minor Axis: | 3 in. |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|------------|
| NEC/(UL) Specification: | CM |
| CEC/(UL) Specification: | CM |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)

Nom. Inductance:

Inductance (µH/ft)

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)

Nominal Velocity of Propagation:

VP (%)

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 15.900 Ohm/1000 ft

Max. Operating Voltage - UL:

Voltage

Max. Recommended Current:

Current

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|---------------|----------|-------------|--------------|-------|---------------------------|
| 1509C B591000 | 1,000 FT | 46.000 LB | BLACK, MATTE | C | 2 PR #24 PO FS PVC FS PVC |
| 1509C B59500 | 500 FT | 24.000 LB | BLACK, MATTE | C | 2 PR #24 PO FS PVC FS PVC |

Notes:

C = CRATE REEL PUT-UP.

1509C Multi-Conductor - Flexible, CM Rated Cable

Revision Number: 1 Revision Date: 10-03-2012

© 2015 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.