

1694D Coax - Dual RG-6/U Type Precision Low Loss Serial Digital Video coax



For more Information
please call

1-800-Belden1



General Description:

Dual RG-6/U type, (2) 18 AWG solid .040" bare copper conductors, gas-injected foam HDPE insulation, Duofoil® plus tinned copper braid shield (95% coverage), inner PVC jackets, overall PVC jacket.

Usage (Overall)

Suitable Applications: Video Mult.

Physical Characteristics (Overall)

Conductor

AWG:

| # Coax | AWG | Stranding | Conductor Material | Dia. (in.) |
|--------|-----|-----------|--------------------|------------|
| 2 | 18 | Solid | BC - Bare Copper | 0.040 |

Total Number of Conductors: 2

Insulation

Insulation Material:

| Insulation Material | Dia. (in.) |
|---|------------|
| Gas-injected FHDPE - Foam High Density Polyethylene | .180 |

Inner Shield

Inner Shield Material:

| Layer # | Inner Shield Trade Name | Type | Inner Shield Material | Coverage (%) |
|---------|-------------------------|-------|--|--------------|
| 1 | Duofoil® | Tape | Aluminum Foil-Polyester Tape-Aluminum Foil | 100 |
| 2 | | Braid | TC - Tinned Copper | 95 |

Inner Jacket

Inner Jacket Material:

| Inner Jacket Material | Nom. Dia. (in.) |
|--------------------------|-----------------|
| PVC - Polyvinyl Chloride | .275 |

Inner Jacket Color Code Chart:

| Number | Color |
|--------|-------|
| 1 | Red |
| 2 | Green |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|--------------------------|
| PVC - Polyvinyl Chloride |

Overall Cable

Overall Nominal Diameter: 0.344 x 0.618 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +75°C

UL Temperature Rating: 60°C

Non-UL Temperature Rating: 75°C

Bulk Cable Weight: 124 lbs/1000 ft.

Max. Recommended Pulling Tension: 177 lbs.

Min. Bend Radius/Minor Axis: 3.500 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (ROHS II): Yes

1694D Coax - Dual RG-6/U Type Precision Low Loss Serial Digital Video coax

| | |
|---------------------------------------|------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 04/09/2010 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| RG Type: | 6/U |

Flame Test

| | |
|----------------|-----------------------|
| UL Flame Test: | UL1666 Vertical Shaft |
|----------------|-----------------------|

Suitability

| | |
|------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | Yes |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

| |
|-----------------|
| Impedance (Ohm) |
| 75 |

Nom. Capacitance Conductor to Shield:

| |
|---------------------|
| Capacitance (pF/ft) |
| 16.2 |

Nominal Velocity of Propagation:

| |
|--------|
| VP (%) |
| 82 |

Nominal Delay:

| |
|---------------|
| Delay (ns/ft) |
| 1.24 |

Nom. Conductor DC Resistance:

| |
|--------------------------|
| DCR @ 20°C (Ohm/1000 ft) |
| 6.4 |

Nom. Inner Shield DC Resistance:

| |
|--------------------------|
| DCR @ 20°C (Ohm/1000 ft) |
| 2.800 |

Nom. Attenuation:

| Freq. (MHz) | Attenuation (dB/100 ft.) |
|-------------|--------------------------|
| 1.000 | 0.240 |
| 3.580 | 0.440 |
| 5.000 | 0.520 |
| 7.000 | 0.610 |
| 10.000 | 0.710 |
| 67.500 | 1.650 |
| 71.500 | 1.690 |
| 88.500 | 1.860 |
| 100.000 | 1.950 |
| 135.000 | 2.240 |
| 143.000 | 2.300 |
| 180.000 | 2.570 |
| 270.000 | 3.170 |
| 360.000 | 3.690 |
| 540.000 | 4.600 |
| 720.000 | 5.380 |
| 750.000 | 5.500 |
| 1000.000 | 6.420 |
| 1500.000 | 7.990 |
| 2000.000 | 9.370 |
| 2250.000 | 10.010 |
| 3000.000 | 11.780 |
| 4500.000 | 15.700 |

1694D Coax - Dual RG-6/U Type Precision Low Loss Serial Digital Video coax

Max. Operating Voltage - UL:

| |
|----------------|
| Voltage |
| 300 V RMS |

Other Electrical Characteristic 1: Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination.

Other Electrical Characteristic 2: Return Loss tested in accordance with ASTM D-4566 paragraph 45.3, using a 75 Ohm fixed bridge and termination.

Minimum Structural Return Loss:

| Start Freq. (MHz) | Stop Freq. (MHz) | Min. SRL (dB) |
|-------------------|------------------|---------------|
| 5.000 | 1600.000 | 23.000 |
| 1600.000 | 4500.000 | 21.000 |

Sweep Test

Sweep Testing: Sweep tested 5 MHz to 4.5 GHz.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|---------------|----------|-------------|-------|-------|--------------------------------|
| 1694D 0101000 | 1,000 FT | 131.000 LB | BLACK | C | 2 #18 PE SH PVC FRPVC PARA PVC |
| 1694D 010500 | 500 FT | 66.000 LB | BLACK | | 2 #18 PE SH PVC FRPVC PARA PVC |

Notes:
C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 05-10-2013

© 2015 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.