

# Micro Converter HDMI to SDI



Take the HDMI output from laptop computers or consumer cameras and convert it to SDI for use with broadcast switchers, routers, monitors and more! The multi rate 3G-SDI automatically switches between all SD and HD formats up to 1080p60. You get 2 SDI outputs, support for Level A and Level B equipment, and power over USB!

\$85

## Connections

## **SDI Video Output**

Automatically matches the SD, HD or 3G-SDI HDMI video input

#### **HDMI**

HDMI Type A in


#### Multi Rate Support

Auto detection of SD or HD

# **Updates, Configurations and Power** Micro USB

## Reclocking

Yes



## Standards

#### **SDI Format Support**

525i29.97 NTSC, 625i25 PAL

#### **HD Format Support**

720p50, 59.94, 60 1080p24, 25, 29.97, 30, 50, 59.94, 1080i50, 59.94, 60

## SDI Compliance

SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 372M, SMPTE 425M

#### **SDI Video Rates**

SDI video connections are switchable between standard definition and high definition, and user selectable level A and B via setup utility.

#### **SDI Color Precision**

4:2:2

#### **SDI Color Space**

YUV and RGB

## **SDI Auto Switching**

Automatically detects SD, HD and 3G-SDI

#### **HDMI Format Support**

525i29.97 NTSC, 625i25 PAL 720p50, 59.94, 60 1080p24, 25, 29.97, 30, 50, 59.94, 60 1080i50, 59.94, 60

#### **HDMI Color Precision**

4:2:2

### **HDMI Color Space**

YUV and RGB

## Software

#### **Software Control**

Mac OS X<sup>™</sup> and Windows<sup>™</sup> software upgrade via micro USB

## Internal Software Upgrade

Via micro USB

# **Operating Systems**



Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan or later.



Windows 8.1 or Windows 10.

# **Settings Control**

Via software utility

# Power Requirements

## **Power Supply**

+5V universal power supply included with international socket adapters for all countries.

# **Power Consumption**

2.0 Watts

# Operational Voltage Range

4.4 to 5.25V DC

# **Physical Specifications**



# **Environmental Specifications**

## Operating temperature

0° to 40° C (32° to 104° F)

# Storage temperature

-20° to 60° C (-4° to 140° F)

## **Relative Humidity**

0% to 90% non-condensing

## What's Included

Micro Converter HDMI to SDI

+5V universal power supply with international socket adapters

Warranty	
3 Year Limited Manufacturer's Warranty	
All items on this website are copyright Blackmagic Design Pty. Ltd. 20 All trademarks are property of their respective owners. MSRP exclud	
Blackmagic Design Authorized Reseller	