


## Micro Converter SDI to HDMI



Convert from SDI to HDMI so you can output video from professional SDI video equipment to consumer HDMI televisions, projectors and more! The multi rate 3G-SDI automatically switches between all SD and HD formats up to 1080p60. You also get 3G-SDI loop through, support for Level A and Level B equipment, and power over USB!

**\$85**

### Connections

#### SDI Video Input

1 x SD, HD or 3G-SDI

#### HDMI Output

HDMI Type A out

#### Updates, Configurations and Power


Micro USB

#### SDI Video Output

1 x SDI loop out

#### Multi Rate Support

Auto detection of SD or HD



### Standards

#### SDI Format Support

525i29.97 NTSC, 625i25 PAL

#### HD Format Support

720p50, 720p59.94, 720p60  
1080p24, 1080p25, 1080p29.97, 1080p30,  
1080p50, 1080p59.94, 1080p 60  
1080PsF25, 1080PsF29.97, 1080PsF30  
1080i50, 1080i59.94, 1080i60

#### SDI Compliance

SMPTE 259M, SMPTE 292M, SMPTE 296M,  
SMPTE 372M, SMPTE 425M

#### SDI Video Rates

SDI video connections are switchable between standard definition, high definition level A and level B 3G-SDI

#### SDI Color Precision

4:2:2

#### SDI Color Space

YUV and RGB

#### SDI Auto Switching

Automatically detects SD, HD and 3G-SDI

#### HDMI Format Support

525i29.97 NTSC, 625i25 PAL  
720p50, 59.94, 60  
1080p24, 25, 29.97, 30, 50, 59.94, 60  
1080i50, 59.94, 60

#### HDMI Color Precision

4:2:2

#### HDMI Color Space

YUV

---

## Software

### Software Control

Mac OS X™ and Windows™ software upgrade via micro USB

### Internal Software Upgrade

Via micro USB

---

## Operating Systems



Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan or later.



Windows 8.1 or Windows 10.

---

## Settings Control

Via software utility

---

## Power Requirements

### Power Supply

+5V universal power supply included with international socket adapters for all countries.

### Power Consumption


1.60 Watts

### Operational Voltage Range

4.4V to 5.25V DC

---

## Physical Specifications



## Environmental Specifications

### Operating temperature

0° to 40° C (32° to 104° F)

### Storage temperature

-20° to 60° C (-4° to 140° F)

### Relative Humidity

0% to 90% non-condensing

---

## What's Included

Micro Converter SDI to HDMI

+5V universal power supply with international socket adapters

---

---

## Warranty

3 Year Limited Manufacturer's Warranty.

---

All items on this website are copyright Blackmagic Design Pty. Ltd. 2016, all rights reserved.  
All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.

Blackmagic Design Authorized Reseller