

MODEL #

**MP70**

NETWORK-READY

*Digital Signage Player***H.264****ENHANCED  
BITRATES****1080p****HDMI™****3D  
READY**

A simple, yet powerful, network-ready digital signage player that provides the flexibility and reach needed for intricate digital signage systems, while keeping cost minimal. An essential component for digital signage systems needing network capability without having all the bells and whistles unnecessarily added.

### • — KEY FEATURES — •

- Enhanced bitrate playback for Blu-ray quality 1080p output
- Integrated Webkit browser with proprietary video plugin for dynamic, easily programmable screen layouts using HTML
- Full featured playlist with advanced multi-playlist scheduling for a variety of media files
- Industrial grade metal chassis
- Reprogrammable timer, auto start, loop video, slide show features
- API for writing unique applications that are executed for special display control applications
- 75% lower power consumption than that of a PC
- 3D ready



### • — SPECIFICATIONS — •

<b>Video Output:</b>	HDMI™ up to 1080p
<b>Status Display:</b>	Power LED
<b>Audio Output:</b>	Digital: Embedded in HDMI™ Digital/Toslink: Optical (Optional factory installed Output at time of order)
<b>Control I/O:</b>	SD card (Accessible) • 2.0 (up to 32GB) USB 2.0 • Host x 1 IR Sensor • Remote Control
<b>Network Connection:</b>	LAN: 10/100 BASE-T WiFi: 802.11 b/g/n (USB optional)
<b>Video Format Support:</b>	MPEG2: MP@HL (35 Mbps max HD) MPEG4.2: ASP@L5 MPEG4.10 (H.264): MP@L4.0 WMV9: 20Mbps max VC-1: AP@L3 Note: While player supports data rates up to 40Mb/s, it is best to average 35Mb/s or less for optimum performance
<b>Graphics Format:</b>	JPEG: Baseline, Progressive, GIF, PNG Recommended resolution 1366x768 full screen
<b>Audio Format:</b>	MPEG1: Layers I, II, III (MP3) 2.0 MPEG4: AAC-LC 5.1, HE-AAC 5.1 WMA9: w2.0
<b>Accessories:</b>	Remote Control • Quick Start Guide Dolby Digital License v.5.1

### • — RECOMMENDED NETWORK SETUP — •

<b>Bandwidth:</b>	DSL • Cable • T1(128 Kbps. minimum) VSAT may work with custom setup
<b>TCP/IP Address:</b>	LAN: Any fixed IP address for each player WAN: Fixed public IP address for each player or router with its port forwarding enabled if players are behind a router
<b>Required Ports for SNMP API:</b>	Player port is fixed at 161 Source port 161 Player IP Destination Port 161
<b>Storage Options:</b>	Standard: 8 GB SD Card Optional: 8, 16, 32, GB SD Card USB Port: uses 2 to 32 GB USB drive
<b>Network Protocol Support:</b>	IP•TCP•UDP•ICMP•ARP•DHCP•HTTP•FTP IGMP•RTP•SNMP•NTP•DNS
<b>Power:</b>	Input voltage: 12VDC Power dissipation: 6 watts (max) AC/DC Adapter: 100-240 V 50/60Hz
<b>Environment:</b>	Operating Temp: 0 – 40° C Operating Humidity: 80% max, relative humidity, non-condensing
<b>General:</b>	Dimensions: 1" H x 6.0" W x 2.9" D Unit Weight: 1.4 lbs