



Beamer-V

Fiber optic transmission of composite video in a simple, low-cost system

Ideal Applications:

Security, A/V Confidence Monitoring



Signal	Channels	Direction
3100/3101 Video	1	→
3108A/3109A Video	Dual	→

Features

Transmits up to three kilometers over multimode fiber at 850 nm

8 MHz video bandwidth

May be purchased as a complete, low cost system including transmitter, receiver and two power supplies

Card version supports dual video channels

Card version fills one slot in 6000A card cage

Fiber is immune to the effects of electrical interference, ground loops, explosive and hazardous environments, moisture and high voltage

Ordering Information

Part Number	Description	Fiber Cores
3100	Transmitter Box	1
3101	Receiver Box	1
3105-pp	Beamer-V System: Includes 1 Transmitter Box, 1 Receiver Box and 2 Power Supplies	1
3108A	Dual Channel Transmitter Card	2
3109A	Dual Channel Receiver Card	2
119757	N. American Power Supply: 115 volts AC to 12 volts DC with connector	
102202	European Power Supply: 230 volts AC to 9 volts DC with connector	
119854	United Kingdom Power Supply: 230 volts AC to 9 volts DC with connector	
121016	Japanese Power Supply: 100 volts AC to 9 volts DC with connector	

Power Supply Suffix Codes (pp):

NA - North America AU - Australia EU - Europe
JP - Japan UK - United Kingdom

Sales



CSI Communications
Specialties, Inc.

631-273-0404 | commspecial.com
info@commspecial.com



Beamer-V



Schedule
Contract GS-03F-5063C



Operating Loss Budget & Maximum Usable Distance*

Wavelength	Loss(dB)	Distance (km)
850 MM	0-12	0-3

* Distance specifications are only approximate and are not guaranteed. Operating loss budget must not be exceeded.

Want to learn more about fiber?

Log on to commspecial.com
for fiber related resources written
for Pro A/V Professionals by
Pro A/V Professionals!



Backed by a 30-day satisfaction
guarantee and a three-year limited
warranty on parts and labor.
See website for terms and conditions.

Sales



CSI Communications
Specialties, Inc.

631-273-0404 | commspecial.com
info@commspecial.com

UPDATED 2/6/2009

All specifications subject to change without notice. © 2009

Fiberlink and the starburst logo are registered trademarks of
Communications Specialties, Inc. CSI and the triangle designs
are trademarks of Communications Specialties, Inc.



Video Specifications

Number of Channels	1
Number of Outputs per Channel	Box: 1; Card: 2
Bandwidth	8 MHz
Input/Output Impedance	75 Ohms
Signal-to-Noise Ratio (per RS-250)	52 dB minimum
Differential Gain (per RS-250)	2% typical
Differential Phase (per RS-250)	1° typical
Input/Output Voltage	1 volt p-p (user adjustable at receiver)

General Specifications

Number of Fibers	Box: 1; Card: 2 (1 per channel)
Operating Temperature	-35 to +75° C
Relative Humidity	10 to 90%, non-condensing
Operating Power (per unit)	9-12 V \pm 10% DC @ 100 ma max.
Dimensions	3.25 L x 2.38 W x 1 H (inches) 83 L x 60 W x 25.4 (mm)
Weight	3.0 oz. (85.04 grams)
Optical Connectors	ST
Optical Wavelength	850 nm
Optical Fiber	62.5 micron multimode fiber

About CSI

Communications Specialties, Inc. (CSI) is an award-winning manufacturer of Pro A/V products for the distribution, conversion or transmission of television and computer video signals, including fiber optic transmission systems, scan converters and video scalars. The company was founded in 1983 by veterans of the broadcast industry. Since then, CSI has managed to consistently design innovative products that are used worldwide by Fortune 500 Companies in a variety of markets such as Broadcast/Professional A/V, Video Conferencing, Education, Home Theater, Security, ITS, Industrial Monitoring, and more!

The **Fiberlink**® line offers an extensive and affordable family of fiber optic transmission systems for the Professional A/V marketplace and includes several ground-breaking products for the transmission of high-resolution RGB signals. Systems for point-to-point and point-to-multipoint signal distribution make these products highly desirable for any Pro A/V architecture. New products are constantly being designed and developed and you can get the latest information at commspecial.com

Also from CSI: Scan Do® Scan Converters and Deuce® Video Scalars