



6000A Rackmountable Card Cage

3 RU high enclosure with 20 positions for any combination of Fiberlink card modules. Power supply and alarm sensing module available.



Ordering Information

| Part Number | Description | Number of Positions |
|-------------|---|---------------------|
| 6000A | Rackmountable Card Cage | 20 |
| 6010A-pp | 85 Watt Universal Switching Power Supply | 3 |
| 6012A-pp | 150 Watt Universal Switching Power Supply | 3 |
| 6020A | Alarm Sensing Module | 1 |
| 6031 | Single Filler Panel | 1 |
| 6032 | Double Filler Panel | 2 |
| 6034 | Quadruple Filler Panel | 4 |

Power Supply Suffix Codes (pp) for AC Line Cord:

| | | |
|--------------------|---------------------|-------------|
| NA - North America | AU - Australia | EU - Europe |
| JP - Japan | UK - United Kingdom | |

Features

Rackmountable 19" card cage offers 20 positions for any combination of Fiberlink transmitter, receiver and transceiver card modules. (Please refer to the Fiberlink® products' data sheet for slot and power requirements)

Cage may be powered with optional 3-position plug-in power supply or with an external, customer-provided power source

Two power supplies may be used to provide redundant power

Optical signal input and output connectors on each card module are at the rear of the card cage

Optional alarm module indicates fault condition via an audible piezo sounder, blinking red LED and activation of isolated contacts for use with remote monitoring

Single and multiple position blank filler panels are available to conceal positions not in use

ROHS Compliant

About CSI

Communications Specialties, Inc. (CSI) is an award-winning manufacturer of Pro A/V products for the distribution, conversion or transmission of television and computer video signals, including fiber optic transmission systems, scan converters and video scalars. The company was founded in 1983 by veterans of the broadcast industry. Since then, CSI has managed to consistently design innovative products that are used worldwide by Fortune 500 Companies in a variety of markets such as Broadcast/Professional A/V, Videoconferencing, Education, Home Theater, Security, ITS, Industrial Monitoring, and more!

Also from CSI: Scan Do® Scan Converters and Deuce® Video Scalars

Sales



631-273-0404 | commspecial.com
info@commspecial.com



6000A Card Cage



Card Cage Specifications:

| | |
|----------------------------------|---|
| Total Number of Positions | 20 |
| Finish | Clear, irridited aluminum |
| Physical Size | 19 W x 5.25 H x 11 D (inches) 483 W x 133 H x 280 D (mm) |
| Operating Temperature Range | -35° C to +75° C |
| Optional External Power Input* | 8.7 to 12 VDC |
| Max. Allowable External Current* | 11 amperes |
| External Power Input Connector | 3 position terminal block |

*The external power input connector is reverse-polarity protected but should be current limited and/or fused so that input current cannot exceed a maxium of 11 amperes

6010A Universal Switching Power Supply Specifications:

| | |
|----------------------------------|--|
| Total Number of Positions | 3 |
| Input Voltage Range (continuous) | 90 to 260 volts AC 47 to 63 Hz @ 2A max. |
| Output Power | 8.0 volts DC +/-5% regulated @ 11 A max. |
| Output Protection | Overvoltage; crowbar, short circuit; current limiting |
| Input Protection | A/C Fuse for catastrophic failure |
| Ripple and Noise | 1% p-p, DC to 20 MHz |
| Operating Temperature Range | -20° C to +70° C; Derate linearly from 100% load at 50° C to 50% load at 70° C |
| Input Power Connector | IEC 320 |
| Efficiency | 85% |
| MTBF | 100,000 Hours |

6012A Universal Switching Power Supply Specifications:

| | |
|----------------------------------|--|
| Total Number of Positions | 3 |
| Input Voltage Range (continuous) | 90 to 260 volts AC 47 to 63 Hz @ 2A max. |
| Output Power | 15 volts DC +/-5% regulated @ 10 A max. |
| Output Protection | Overvoltage; crowbar, short circuit; current limiting |
| Input Protection | A/C Fuse for catastrophic failure |
| Ripple and Noise | 1% p-p, DC to 20 MHz |
| Operating Temperature Range | -20° C to +70° C; Derate linearly from 100% load at 50° C to 50% load at 70° C |
| Input Power Connector | IEC 320 |
| Efficiency | 88% |
| MTBF | 100,000 Hours |

Alarm Sensing Module Specifications:

| | |
|---------------------------|---|
| Total Number of Positions | 1 |
| Alarm Indications* | Blinking red LED, pulsing piezo sounder, external SPDT contact closures |
| External Contact Ratings | 115/230 VAC 50/60 Hz 5 amperes resistive |

* Note that the audible piezo sounder can be turned off via a front panel switch. The blinking red alarm LED and the activated external contacts cannot be deactivated until the fault condition is corrected.

Want to learn more about fiber?

Log on to commspecial.com for fiber related resources written for Pro A/V Professionals by Pro A/V Professionals!



Backed by a 30-day satisfaction guarantee and a three-year limited warranty on parts and labor. See website for terms and conditions.

Sales



CSI Communications Specialties, Inc.
631-273-0404 | commspecial.com
info@commspecial.com

UPDATED 6/13/2012

All specifications subject to change without notice. © 2012

Fiberlink and the starburst logo are registered trademarks of Communications Specialties, Inc. CSI and the triangle designs are trademarks of Communications Specialties, Inc.

