



75Ω Digital Video Coaxial Cable

L-CFB precision digital video cable, offers the professional Broadcaster a high performance, 100% Sweep Tested, low cost, low loss coax that meets the demands of today's facility migration trends toward Serial Digital Video and HDTV standards.

Applications

- SD-SDI/HD-SDI
- Satellite headends
- Broadband facilities

Features

1. 75 Ohm impedance
2. ≥ 20 dB return loss to 2GHz
3. Solid annealed copper center conductor
4. Tinned copper braid shield, aluminum foil, foam polyethylene dielectric

Benefits

1. Professional standard
2. Superior performance
3. Specifically designed for digital and HDTV facilities
4. Extremely low signal loss

L-2.5CFB

25 AWG
Micro coax type

L-3CFB

22 AWG
Mini coax type

L-4CFB

20 AWG
RG59 type

L-5CFB

18 AWG
RG6 type

L-7CFB

15 AWG
RG11 type

Serial Digital Cable

Serial Digital video signals are transmitted at very high data bit rates and should be handled quite differently than traditional baseband analog video lines. Typical digital frequency platform bandwidths range from 143 MHz for Composite digital video, 270 MHz for Component digital video and 360 MHz for the proposed HDTV rate.

Commonly used 75Ω coaxial cables like RG59 and 8281 are generally acceptable for analog baseband video and may even be used for short runs of digital video transmission. But, in a modern facility system design, where new **SERIAL DIGITAL** equipment installations require long tie lines and multiple I/O's, it is important to consider the 75Ω Coaxial Cable selection along with **"Impedance Matching" BNC Connectors and Patchbays** to maximize the overall electrical length and achieve optimum results.

Mechanical Specifications										Electrical Performance				
Model	Std. Lng.	Wt/Std. Lng. lbs (kgs)	Nom O.D. Inch (mm)	PVC Jkt Thick Inch (mm)	Brittle Point °F °C	Cond Mat AWG	Insul O.D. Inch (mm)	Cond. O.D. Inch (mm)	Shield Coverage	Cond. D.C.R. Ω/1000ft Ω/100m	Shield D.C.R. Ω/1000ft Ω/100m	Nom Cap (1KHz) pF/ft pF/m	Velocity of Prop.	SD Trans Lng@270 Mb/s*
L-2.5CFB	984ft 300m	17	0.157	0.020	-22 -30	Bare Copper	0.094	0.094	TAC >92%	<28.35	<7.3	17 55	79%	470 ft min
		7	4.0	0.5		25	2.4	2.4	AL Foil 100%	<9.3	<2.4			614 ft max
L-3CFB		29	0.217	0.035		Bare Copper	0.122	0.122	TAC >91%	<16.8	<4.3			650 ft min
		13	5.5	0.9		22	3.1	3.1	AL Foil 100%	<5.5	<1.4			830 ft max
L-4CFB		33	0.240	0.035		Bare Copper	0.146	0.146	TAC >93%	<11.0	<3.0			710 ft min
		15	6.1	0.9		20	3.7	3.7	AL Foil 100%	>3.6	<1.0			920 ft max
L-5CFB	49	0.303	0.043	Bare Copper	0.192	0.192	TAC >93%	<7.0	<2.1	940 ft min				
	22	7.7	1.1	18	4.9	4.9	AL Foil 100%	<2.3	<0.7	1210 ft max				
L-7CFB	86	0.402	0.039	Bare Copper	0.287	0.287	TAC >96%	<3.1	<1.4	1280 ft min				
	39	10.2	1.0	15	7.3	7.3	AL Foil 100%	<1.0	<0.5	1660 ft max				

Foam Polyethylene dielectric insulation. Dielectric strength = 1000V AC / 1min.
Insulation resistance/3Mft =>1000MegaOhms. *For reference only.

		Nominal Attenuation Value									
		10 MHz	67.5 MHz	135 MHz	270 MHz	360 MHz	750 MHz	1.0 GHz	1.5 GHz	2 GHz	2.4 GHz
L-2.5CFB	dB/100 ft	1.3	3.5	4.9	7.0	8.1	11.1	12.8	15.7	18.1	19.9
	dB/100 m	4.4	11.4	16.2	22.9	26.4	36.4	42.0	51.5	59.4	65.1
L-3CFB	dB/100 ft	1.0	2.7	3.8	5.4	6.2	8.5	9.8	12.0	13.8	15.2
	dB/100 m	3.4	8.8	12.5	17.7	20.4	27.7	32.0	39.2	45.2	49.6
L-4CFB	dB/100 ft	0.9	2.3	3.3	4.6	5.3	7.7	8.9	10.8	12.5	13.7
	dB/100 m	2.9	7.5	10.7	15.1	17.4	25.1	29.0	35.5	41.0	44.9
L-5CFB	dB/100 ft	0.7	1.7	2.5	3.5	4.0	5.8	7.2	8.9	10.6	11.6
	dB/100 m	2.2	5.7	8.1	11.4	13.2	19.1	23.7	29.0	34.8	38.1
L-7CFB	dB/100 ft	0.5	1.3	1.9	2.7	3.1	4.5	5.2	6.3	7.3	8.0
	dB/100 m	1.7	4.4	6.2	8.8	10.2	14.6	16.9	20.6	23.8	26.1