

Ovation™ F-165WW



Powered by 16 10-watt LEDs, Ovation™ F-165WW delivers a smooth, even wash with a warm color temperature and a beautiful soft field. It also features an easily adjustable, motorized zoom with a range from 25° to 76° and can accommodate barn doors for glare reduction and beam shaping. Selectable dimming curves make it compatible with older, traditional theatre Fresnels.

FEATURES

- 16-bit dimming resolution for smooth fades
- Flat, even field of light
- Virtually silent operation for use in any situation
- Simple and complex DMX channel profiles for programming versatility
- Warm white Fresnel-style lighting fixture
- Motorized zoom angle between 25° to 76°, manually or via DMX

SPECIFICATIONS

- DMX Channels: 1, 2 or 5
- Data Connectors: 3- and 5-pin XLR
- Light Source: 16 LEDs (WW) 10 W, (2.8 A), 100,000 hours life expectancy
- Accessory Holder/
Gel Frame Size: 7.5 in (191 mm)
- Dimmer: Electronic
- Focus: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Beam Angle: 14° to 55°
- Field Angle: 25° to 76°
- Zoom Angle: 25° to 76°
- Dimming Modes: 9
- Lumens (25°): 2,661
- Lumens (76°): 6,481
- Illuminance (25°): 1,860 lux @ 5 m
- Illuminance (76°): 285 lux @ 5 m
- Color Temperature (at full): 3184 K
- Max. Noise Level (studio): 41 dB @ 12 in (305 mm)
- Max. Noise Level (power): 45 dB @ 12 in (305 mm)
- Max. Noise Level (live): 43 dB @ 12 in (305 mm)
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 5 units @ 120 V; 9 units @ 208 V; 10 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 170 W, 1.41 A @ 120 V, 60 Hz
- Power and Current: 166 W, 0.85 A @ 208 V, 60 Hz
- Power and Current: 166 W, 0.78 A @ 230 V, 50 Hz
- Weight: 14.6 lb (6.6 kg)
- Dimensions: 16.5 x 11 x 10 in (418 x 283 x 255 mm)
- Approvals: CE, MET