

# Rogue™ R1 Wash



New to the Rogue™ family, a powerful wash unit with smooth color blending for stunning visual effects. Meet the Rogue™ R1 Wash, a versatile and bright LED wash that is guaranteed to give you the coverage you need at the speed you require. Rogue™ R1 Wash features smooth pan and tilt operation, an 11° to 48° zoom range that gives you the spread to cover the gamut of entertainment genres, and a unique lens system that gives you an even, professionally combined wash of color.

## FEATURES

- 7 RGBW LEDs, 15 W each
- 3- and 5-pin DMX input/output connections
- Unique lens design for excellent color blending
- Fast, smooth pan and tilt movement
- 6 distinct dimming modes for advanced control
- Omega mounting bracket, fits all Rogue™, Next™, and Legend™ fixtures
- Easy to read OLED display with simple, effective menu options
- Simple and complex DMX channel profiles for programming versatility

## SPECIFICATIONS

- DMX Channels: 14, 15, 19 or 21
- Data Connectors: 3- and 5-pin XLR
- Light Source: 7 LEDs (quad-color RGBW)  
15 W, (980 mA), 50,000 hours life expectancy
- Pan and Tilt: 540°/230°
- Pan and Tilt Ranges: 180°, 360°, 540° pan/  
90°, 180°, 230° tilt
- Automatic Pan/Tilt Correction: Yes
- Built-in Automated Programs: Yes
- Customizable Programs: No
- Recall Custom Programs: No
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Beam Angle: 8° to 30°
- Field Angle: 11° to 48°
- Zoom Angle: 11° to 48°
- Dimming Modes: 6
- Illuminance (11°): 3,098 lux @ 5 m
- Illuminance (48°): 299 lux @ 5 m
- Color Temperature (range): 2800 to 10000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 10 units @ 120 V; 18 units @ 208 V; 21 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 161 W, 1.34 A @ 120 V, 60 Hz
- Power and Current: 141 W, 0.72 A @ 208 V, 60 Hz
- Power and Current: 139 W, 0.62 A @ 230 V, 50 Hz
- Weight: 13 lb (5.9 kg)
- Dimensions: 7.36 x 10.43 x 13.94 in (187 x 265 x 354 mm)
- Approvals: CE, MET