

# iEQ™ 15

Dual 15-Band Digital Graphic Equalizer/Limiter with TYPE V™ NR and AFS™

**dbx**®

PROFESSIONAL PRODUCTS

## VISIONARY DESIGN

With an EQ heritage that has produced countless industry standard patents and dates back more than 30 years, the dbx iEQ-31 easily lives up to the dbx legacy of uncompromised sonic integrity. In addition to unsurpassed equalization specs, the iEQ-15 also offers the built-in necessities which include AFS™ feedback Suppression, Type V™ noise reduction and PeakStopPlus® limiting. Besides including two 15-band channels of 2/3-octave equalization, the iEQ-15 also offers  $\pm 12$  dB input gain range; switchable  $\pm 6$  or  $\pm 15$  dB boost/cut range, 40mm faders, XLR, 1/4" and Euroblock inputs and outputs, nonconductive nylon sliders; and an intuitive user interface with comprehensive output and gain reduction metering. As always, the inevitable result of our meticulous attention to detail and top-quality componentry is exceptional sound, performance, and reliability.

## REVOLUTIONARY ENGINEERING

The iEQ series represents a major step forward in the performance of EQs. The iEQ series is now able to offer state-of-the-art digital EQ performance and specs with an analog look and feel. From its amazing 10Hz to 22kHz frequency response, to its 113dB dynamic range and Advanced Feedback Suppression (AFS™), dbx proprietary Type V™ noise reduction and PeakStopPlus® limiting, the iEQ-15 offers out of this world specifications with a down-to-earth price point. Sure to find a home in the studio, on tour and with installed sound venues, the iEQ-15 is destined to take its rightful place in the lineage of great dbx® signal processors that are the professional's choice in signal processing. With such pristine design and quality, the iEQ-15 offers the maximum sonic flexibility in a straight forward interface and rock-solid construction. For more information please visit us at: [www.dbxpro.com](http://www.dbxpro.com).

## FEATURES

- **Advanced Feedback Suppression (AFS™)**
- **Type V™ Noise Reduction**
- **PeakStopPlus® Limiting**
- **2/3-octave Constant Q frequency bands**
- **Switchable boost/cut ranges of  $\pm 6$  or  $\pm 15$  dB**
- **18 dB per octave 40Hz low-cut filter**
- **$\pm 12$  dB input gain range**
- **XLR, TRS and Euroblock Inputs and Outputs**
- **Internal Toroidal Transformer**
- **Dynamic range of greater than 113dB**
- **User Power Up Features**
- **Relay Bypass for Power Failure System Protection**

8760 S. Sandy Pkwy.  
Sandy, Utah 84070  
Phone (801) 568-7660  
Fax (801) 568-7662  
Int'l Fax (801) 568-7583  
[customer@dbxpro.com](mailto:customer@dbxpro.com)  
<http://www.dbxpro.com>

**H** A Harman International Company



# iEQ™ 15

Dual 15-Band Digital Graphic Equalizer/Limiter with TYPE V™ NR and AFS™



## SPECIFICATIONS

### Inputs

Connectors: 1/4" TRS, female XLR (pin 2 hot), and Euroblock  
Type: Electronically balanced/unbalanced, RF filtered  
Impedance: Balanced 40k $\Omega$  unbalanced 20k $\Omega$   
Max Input Level: +22dBu balanced or unbalanced  
CMRR: >40dB, typically >55dB at 1kHz

### Outputs

Connectors: 1/4" TRS, male XLR (pin 2 hot), and Euroblock  
Type: Balanced/unbalanced, RF filtered  
Impedance: Balanced 120 $\Omega$  unbalanced 60 $\Omega$   
Max Output Level: +20dBu balanced/unbalanced into 2k $\Omega$  or greater

### System Performance

Frequency Response: 20Hz to 20kHz, +0.5/-0.25dB  
Dynamic Range: >113dB, "A" weighted  
THD+Noise: 0.003% typical at +4dBu, 1kHz  
Interchannel Crosstalk: <-80dB, 20Hz to 20kHz  
Noise Reduction: Up to 10dB of dynamic broadband noise reduction  
Digital Resolution: 24 bits  
Sample Frequency: 48kHz  
Latency: 2msec

### Function Switches

AFS™: Activates dbx AFS™ Advanced Feedback Suppression  
TYPE V™ NR: Activates dbx Type V™ Noise Reduction  
EQ Bypass: Bypasses the graphic equalizer section in the signal path  
Low Cut: Activates the 40Hz 18dB/octave Bessel high-pass filter Range  
Range: Selects either +/- 6dB or +/- 15dB slider boost/cut range

### Indicators

Output Level: 4-LED bar graph (Green, Green, Yellow, Red) at -10, 0, +10, and +18dBu  
Gain Reduction: 4-LED bar graph (all Red) at 0, 3, 6, and 10dB  
Type V™ NR: 1 LED: yellow, green or red  
EQ Bypass: 1 LED: red  
Clip: 1 LED: red  
Low Cut: 1 LED: red  
+/-15dB: 1 LED: red

### Power Supply

Operating Voltage: 120VAC 60Hz, 220-240VAC 50/60Hz  
Power Consumption: 17 Watts  
Mains Connection: IEC receptacle

### Physical

Dimensions: 35" H X 19" W X 7.9" D (89cm x 48cm x 20.1cm)  
Weight: 7.5 lbs.  
Shipping Weight: 8.5 lbs.

dbx engineers are constantly working to improve the quality of our products. Specifications are, therefore subject to change without notice.

### FOR MORE INFORMATION CONTACT:

dbx Professional Products  
8760 S. Sandy Pkwy.  
Sandy, Utah 84070  
Phone (801) 568-7660  
Fax (801) 568-7662  
customer@dbxpro.com  
http://www.dbxpro.com



The Professional's Choice In Signal Processing™

A Harman International Company