

# CONVERTERS & DISTRIBUTION AMPLIFIERS



**DAC-9P Converter »**

## Video/Audio Converters

Datavideo Converters keep your production equipment working together by bridging the gap between otherwise incompatible devices.

Perhaps your new HDMI-input monitor does not accept video from your SDI switcher. Not to worry! Convert it, and bring harmony back to your hardware.



	<b>BAC-03 Audio Converter</b> (\$225 MSRP)	<b>DAC-90 Audio De-Embedder</b> (\$Call\$)	<b>DAC-7 Video Converter</b> (\$280 MSRP)	<b>DAC-8P Video Converter</b> (\$295 MSRP)	<b>DAC-9P Video Converter</b> (\$295 MSRP)
Video Inputs	n/a	2x HD/SD-SDI	1x SD Component YUV, 1x S-Video	1x HD/SD-SDI	1x HDMI
Video Outputs	n/a	2x HD/SD-SDI	2x SD-SDI	1x HDMI	2x HD/SD-SDI
Loop Through	n/a	n/a	n/a	1x HD/SD-SDI	n/a
Audio Inputs	2x RCA (Stereo Pair), 2x XLR (Stereo Pair)	n/a	2x RCA (Stereo Pair), 2x XLR (Stereo Pair)	2x RCA (Stereo Pair)	n/a
Audio Outputs	2x RCA (Stereo Pair), 2x XLR (Stereo Pair)	SetA = 4x XLR (Ch 1-16) SetB = 4x XLR (Ch 1-16)	n/a	n/a	n/a
Audio Embedding	n/a	n/a	RCA & XLR Audio Embedded into SD-SDI Signal	RCA Audio Embedded into HDMI Signal	HDMI Audio Embedded into SDI Signal
Supported Input Resolutions	n/a	n/a	720x480i (NTSC), 720x576i (PAL)	720x480i, 720x576i, 1280x720p (50/59.94/60Hz), 1920x1080i (50Hz/59.94/60Hz), 1920x1080p (50/59.94/60Hz)	720x480i, 720x576i, 1280x720p (50/59.94/60Hz), 1920x1080i (50/59.94/60Hz), 1920x1080p (50/59.94/60Hz)
Output Resolutions	n/a	n/a			
Special Features	• Locking Pwr Connector	• Locking Pwr Connector	• Locking Pwr Connector	• Rack-Mount Kit (Call) • Locking Pwr Connector	• Rack-Mount Kit (Call) • Locking Pwr Connector

## Distribution Amplifiers

If you need to multiply your video/audio signals, a Datavideo Distribution Amplifier is for you. Use them to send video to additional destinations, like waiting rooms, green-screen rooms, and more.



**VP-445  
Distribution  
Amplifier »**



	<b>DAC-50 Video Converter</b> (\$550 MSRP)	<b>DAC-60 Video Converter</b> (\$350 MSRP)	<b>DAC-70 Video Cross-Converter</b> (\$Call\$)	<b>VP-299 Video Distributor</b> (\$120 MSRP)	<b>VP-445 Video Distributor</b> (\$199 MSRP)
Video Inputs	1x HD/SD-SDI	1x 3G/HD/SD-SDI	1x HDMI, 1x HD/SD-SDI, 1x VGA	1x S-Video, 1x Composite Video RCA	1x HD/SD-SDI
Video Outputs	1x HD/SD YUV or 1x Composite Video	1x VGA	2x HD/SD-SDI, 1x HDMI,	4x Composite Video RCA, 4x S-Video	4x HD/SD-SDI
Loop Through	n/a	1x 3G/HD/SD-SDI	1x HD/SD-SDI	n/a	n/a
Audio Inputs	n/a	n/a	1x Stereo RCA Pair	2x RCA (One Stereo Pair)	n/a
Audio Outputs	n/a	n/a	n/a	8x RCA (Four Stereo Pairs)	n/a
Audio Embedding	n/a	n/a	Audio Embedded into HDMI & SDI Signals	n/a	n/a
Supported Input Resolutions	720x480i, 720x576i, 1280x720p (50/59.94Hz), 1920x1080i (50/59.94Hz)	720x480i, 720x576i, 1280x720p (50/59.94), 1920x1080i (50/59.94), 1920x1080p (24/25/30/50/59.94/60Hz)	800x600 (60Hz), 1024x768 (60Hz), 1280x1024 (60Hz), 1366x768 (60Hz), 1400x1050 (60Hz), 1600x1200 (60Hz), 525i, 625i, 1280x720p (50/59.94/60Hz), 1920x1080i (50/59.94/60Hz), 1920x1080p (23.98/24/25/29.97/30/50/59.94/60Hz)	720x480i (NTSC), 720x576i (PAL)	
Output Resolutions	720x480i, 720x576i, 1280x720p (50/59.94Hz), 1920x1080i (50/59.94Hz)	800x600 (60Hz), 1024x768 (60Hz), 1280x1024(60Hz), 1366x768 (60Hz), 1400x1050 (60Hz), 1600x1200 (60Hz)	525i, 625i, 1280x720p (50/59.94/60Hz), 1920x1080i (50/59.94/60Hz), 1920x1080p (50/59.94/60Hz)		
Special Features	• Locking Pwr Connector	• Locking Pwr Connector	• Locking Pwr Connector	• Locking Pwr Connector	• Locking Pwr Connector