


CCTV Lens



Specifications

Auto Iris & Vari-focal Lens

Model No.	Description
EFV-2812DC	Vari-focal 2.8~12 mm auto iris
EFV-358	Vari-focal 3.5~8 mm manual iris
EFV-358DC	Vari-focal 3.5~8 mm auto iris
EFV-416	Vari-focal 4~16 mm manual iris
EFV-416DC	Vari-focal 4~16 mm auto iris
EFV-550	Vari-focal 5~50 mm manual iris
EFV-550DC	Vari-focal 5~50 mm auto iris

Fixed Iris & Mini Board Lens

Model No.	Description
FL-2520	2.5 mm lens
FL-3620	3.6 mm lens
FL-4320	4.3 mm lens
FL-6020	6 mm lens
FL-8020	8 mm lens
FL-1220	12 mm lens
FL-1620	16 mm lens

Master Power Supplies



Features

- Resettable power supplies for all your CCTV cameras*
- UL listed
- Lifetime warranty*
- Available in 4, 8, 16 and 18 outputs in 12VDC or 24VAC

Specifications

Model No.	Description
DCR4-3.5-2UL	Output: 4 / Voltage: 12V / Amps: 4
DCR8-3.5-2UL	Output: 8 / Voltage: 12V / Amps: 4
DCR8-8-2UL	Output: 8 / Voltage: 12V / Amps: 8
DCR16-8-2UL	Output: 16 / Voltage: 12V / Amps: 8
DCR16-12-2UL	Output: 16 / Voltage: 12V / Amps: 16
DCR18-18-1UL*	Output: 18 / Voltage: 12V / Amps: 18
AC4-1-2UL	Output: 4 / Voltage: 24V / Amps: 4.2
AC8-1-2UL	Output: 8 / Voltage: 24V / Amps: 4.2
AC8-2-2UL	Output: 8 / Voltage: 24V / Amps: 8.4
AC16-2-2UL	Output: 16 / Voltage: 24V / Amps: 8.4
AC16-4-2UL	Output: 16 / Voltage: 24V / Amps: 16.8

*Fuse protected and 3 year warranty for DCR18-18-1UL only

Mounting Brackets



Specifications

Dome Brackets

Model	Description
BA-ED	Plastic "L" style mounting bracket for ED series mini domes. 146.7 x 121 x 66 mm / 5.75" x 4.75" x 2.6" (L x W x H)
BA-EHD	Aluminum "L" style mounting bracket for EHD series vandal domes. 169 x 146 x 110 mm / 6.7" x 5.7" x 4.3" (L x W x H)
BA-EDMS	Aluminum "L" style mounting bracket for ED550, ED560, EDN800. 169 x 146 x 110 mm / 6.7" x 5.7" x 4.3" (L x W x H)
BA10	Ceiling mount bracket for EPD200 (624 mm / 24.6" long)
BA11	Ceiling mount bracket for EPD200 (300 mm / 12" long)

Box Camera Brackets

Model No.	Description
BA-01	Mounting bracket. Aluminum. Max. load: 3 kg / 6.6 lbs 57 x 165 mm / 2.2" x 6.5" (W x H)
BA-03	Mounting bracket. Plastic. Max. load: 3.5 kg / 7.7 lbs 80 x 160 mm / 3.1" x 6.3" (W x H)
BA-05	Mounting bracket. Aluminum. Max. load: 10 kg / 22 lbs 84 x 294 mm / 3.3" x 11.6" (W x H)

IR Bullet Camera Brackets

Model	Description
EZ-CMB	"J" style ceiling mount bracket for EZ Series (EZ230E, EZ235E, EZ330E, EZ335E, EZ550). Aluminum, stainless steel 200 x 278.5 mm / 7.8" x 10.9" (W x H)

Camera Housing



Specifications

Model No.	Description
FH-7153	Outdoor camera housing with top cover and lock. Aluminum. 352 x 113 x 106 mm / 13.9" x 4.5" x 4.2" (L x W x H)
FH-7153HB	Outdoor camera housing with top cover, lock, heater and blower. 24VAC, 18.7W power consumption. Aluminum. 373 x 140 x 115 mm / 14.7" x 5.5" x 4.5" (L x W x H)