

EN-75080C

8" Compact LCD Monitor



Features

- Compact size 8" LCD monitor
- Active matrix, TFT, 800x600
- Ideal for mobile applications
- 3D Comb Filter
- Exceptional brightness
- 262,000 colors
- Multi-lingual language support (English, Spanish, French, German, Italian, Portuguese)
- Compatible with VESA™ DDC

Specifications

Screen Size	8"
Viewing Area (mm)	337x270
Pixel Type	Active Matrix TFT
Max. Resolution	800 x 600 @ 60Hz
Pixel Pitch	0.067 x 0.2025 mm
Brightness	250cd/m ²
Contrast Ratio	500:1
Aspect Ratio	4:3
Viewing Angle (H/V)	140°/120°
Display Color	262,000 colors
Response Time	< 25ms (typical)
Video System	NTSC/PAL
Frequency (H)	31 ~ 38 KHz
Frequency (V)	50 ~ 75Hz
Built-in Speakers	Yes (1Wx2)
Gradual Volume Increase	Yes
Video In/Out (BNC Type)	2/2
S-Video In/Out	1/1
VGA In (15 Pin D-Sub)	1
DVI In	No
Audio In/Out (RCA Type)	1/1
PC Stereo In	1
Filter Type	3D Comb Filter/DeInterlace
Dimensions (w/stand)	212.09 x 181.4 x 34 mm/8.35" x 7.14" x 1.34"
Net Weight	1.42 kg / 3.1" lbs
VESA Mounts Size	75x75 mm (BS M4 x 10mm screw)
Parts/Labor	1 year/1 year
MTBF (Approx.)	50,000 hours
Power Consumption	< 15W/Power Saving
Power Source	12VDC, 1.5A

Ordering Information

- **EN-75080C:** 8" LCD monitor, Active Matrix TFT, 800x600, 250 cd/m² Brightness

EN200/EN220

5.6" Color TFT LCD Test Monitor & Service Kit



Features

- 5.6" CCTV test monitor
- Troubleshoot camera display right on installation site
- Full color LCD display to check for video signal
- Small & compact for portability
- Available with monitor service kit

Specifications

Screen Size	5.6", 116 (H) x 87 (V) mm
Active Area (mm)	111.36 (H) x 83.52 (V)
Pixel Type	A-Si Active Matrix TFT
Screen Color	Full color
Dot Matrix	320 (H) x 240 (V) RGB
Dot Pitch	0.116 (H) x 0.348 (V)
Dimension	162 (H) x 133 (V) x 54 (D)
Contrast Ratio	85:1
Luminosity	270cd/m ²
Sound Input	200mW (built-in 4cm speaker)
Terminal Input	Power, video & audio input
Video Input	0.75 VP-p ~ 1 VP-p, 3.5 pin
Audio Input	50mV min., stereo In, 3.5 pin
Stereo Output	Ear phone, 3.5 pin
Screen Display	Reverse/normal switchable (R → N)
Power Consumption	12VDC, 600mA (8W max.)
Power Source	12VDC nominal +/- 10%
Dimensions (W x H x D)	162 x 133 x 54 mm / 6.4" x 5.2" x 2.1"
Operating Temp.	0°C ~ 60°C / 32°F ~ 140°F

Ordering Information

- **EN200:** 5.6" LCD test monitor
- **EN220:** 5.6" LCD test monitor with service kit (pouch, battery pack & clip, cable 1 & 2, AD-3 and AD-4)