

CMS SUB

Professional analog subwoofer

11" (27cm) Polyglass cone subwoofer
Great neutrality for precise adjustment of the bass EQ.

High excursion and /
high efficiency subwoofer
Minute detail retranscription for
precise adjustment of the signal
compression.

Large front laminar port
Constant tone balance,
optimum integration in the
smaller studios.

Numerous settings (low-pass filter +
sound level + entirely adjustable phase,
phase reversal,
Footswitch input, MUTE)
Excellent acoustic coupling between
subwoofer and monitors. Turn to a 2.1
configuration and keep your habits and
marks you acquired with a 2.0 system!

300W rms BASH®
technology amplifier
The class AB amplification
quality combined with
class D efficiency.

LFE / left + right inputs /
left + right outputs
Simplified connections and total
upgrade system possibility
(upgrade from a 2.1 configuration
to a 5.1 without any
extra equipment).

Supplied accessory

Removable grille



CMS SUB

Professional analog subwoofer

Technical specifications

System		CMS SUB
• Frequency response (+/- 3dB)		30Hz - 250Hz
• Maximum SPL		113dB SPL (peak @ 1 m)
Electronic section		
• Input	- Type/Impedance - Connector - Sensitivity	Left, Right, LFE Electronically balanced / 10kOhms Female 3 pins XLR Variable
• Output (to satellites)	- Connector	Left, Right Male 3 pins XLR in parallel on inputs
• Amplifier		300W rms, BASH® technology
• Internal processing and functions	- Subwoofer section	Left + Right mono summation LFE + lo-passed mono sum 24dB/octave variable lo-pass filter Phase adjustment Polarity
• User controls		Sub level (sensitivity) adjustment Lo-pass frequency adjustment Phase adjustment Polarity switch Mute External Mute (controlled by external footswitch)
• Indicators (LED's)		Power on Mute External Mute
• Power supply	- Mains voltage - Connection	230V (T1.6AL fuse rating) or 115V (T3.15AL fuse rating) IEC inlet and detachable power cord
Transducers		
• Subwoofer		Polyglass, high excursion Focal, 270mm (11") drive unit
Cabinet		
• Construction		22mm MDF panels with internal braces
• Finish		Dark grey vinyl
• Dimensions (HxWxD)		435.5mm x 366mm x 440mm (17.1" x 14.4" x 17.3")
• Weight		23kg (50.7lb)