

# MIW-SURGE-1G

## MAX IN-WALL™ SINGLE GANG SURGE PROTECTION

**T**wo AC receptacles provide power protection to remotely located devices. Fits most standard single gang plastic or metal boxes.



### FEATURES

- Decora Faceplate Interface. This piece surrounds the receptacles and fits within a standard cover plates Decora cutout.
- Uses standard wiring device screw-hole.
- Both Outlets with Protect-or-Disconnect Circuitry.
- Bi-color Indicator LED.  
Green = Power On  
Red = Line Fault

### INCLUDES

- Three Wire Nuts
- Two Mounting Screws, (Pre-installed)

- Provides surge protection.
- Mounts behind electronic equipment.
- CSA Certified for code compliant installations.
- 3 Year Product Warranty

### TECHNICAL SPECIFICATIONS

#### AC CIRCUIT

AC Outlets.....	2
Line Voltage.....	120V, 50/60Hz
Total Current Capacity.....	15A
UL 1449 2nd Ed. Suppressed Voltage Rating (@500A) .....	330V
UL 1449 3rd Ed. Voltage Protection Rating (@3000A).....	400V
Protection Modes.....	L-N, L-G, N-G
Energy Dissipation.....	1350 Joules
Protect-or-Disconnect Circuitry.....	Yes

*Specifications subject to change without notice due to product upgrades and improvements.*

#### PRODUCT DIMENSIONS

1.375 in. Width X 4.25 in. Height X 2.25 in. Depth\*

\* Basic Dimensions Only. These do not include cords, plugs, cables, wires, etc.

#### SHIPPING INFORMATION

Single Pack Dimensions.....2.5"W x 2"D x 4.25"H  
Single Unit UPC.....0 50616 00885 3

Inner Pack Qty.....9  
Inner Pack UPC.....30 050616 00885 4

Master Pack Qty.....36  
Master Pack UPC.....50 050616 00885 8

MODEL: MIW-SURGE-1G

DESIGNED & ENGINEERED IN USA • MANUFACTURED IN CHINA



**PFP** Power  
By Panamax-Furman

www.panamax.com www.furmansound.com

L-MIW-SURGE-1G-D 4/12