

POWERED NANO SPOT

NSPA

The Nano Spot is the newest member of the Hot Spot family. Featuring a 3" driver, it has three inputs on the rear panel: XLR, 1/4", and 1/8" stereo summing. With 24V Phantom power, a 20dB pad, and built in compressor, you can go directly into the Nano Spot from your source or microphone. The NSPA can be used in call centers, computer monitoring, on the bar or patio* in a restaurant, and many other applications.

SPECIFICATIONS

3 Inputs: (1) One XLR Balanced,
(2) One 1/4" Balanced/Unbalanced
(3) One 1/8" Stereo Summing

Phantom Power: 24Vdc

Equalizer Controls: Two Band EQ with
Center-Detent Controls

Nominal impedance: 4 ohms

Power Supply: 18Vdc, 1.75A

Built in Amplifier: 25 watts @ 4 ohms

Speaker: 87.5dB @ 1 watt/1 meter

Frequency response: 150Hz-17kHz

Maximum SPL: 101.5dB

Enclosure Materials: High Density ABS

Indicator LEDs: Power, Compressor & Signal

Input Impedance: XLR Input: 4.4 k, Differential Balanced,
1/4" Input: 10 k Balanced,
1/8" Input: 22 k Balanced (11 k Unbalanced)

PAD Switch: 20dB

Built in Compressor

Included: Power supply, Wall and Stand Mount

Color: Black

Dimensions: 5" x 4.25" x 4.5" (127mm x 108mm x 114mm)

Net weight: 1.75 lbs. (0.793kg)



4.5"



5"



**BRACKET
INCLUDED**



Specifications subject to change without notice.

*speaker is not weather proof and should not be installed in an outdoor setting.

601 E. Pawnee Wichita, KS 67211 316. 263.2852 FAX 316.263.0642 www.galaxyaudio.com

Distributed outside the United States by **E and E Exports, Inc.** 2815 Junipero Ave. Suite 101 Signal Hill, CA 92614
562.988.3447 FAX 562.989.3037

Distributed in Canada by **Audio Distributors International (ADI)** 1275 Newton, unit 6 Boucherville, QC J4B 5H2 Canada
450.449.8177 FAX 450.449.8180

MAKERS OF THE ORIGINAL
HOT SPOT PERSONAL MONITOR

V20141031