



TA-PV2J650

V-Mount Adaptor for JVC GY-HM600/GY-HM650



Expanding on the popular ENDURA V-Plate family, IDX introduces the TA-PV2J650. Designed specifically for use with the JVC GY-HM600/GY-HM650 cameras, the TA-PV2J650 plugs directly to the camera and is compatible with IDX A-CP(A) universal mounting plate, TA-CA2 support accessory, and other 3rd party manufactured mounting plates and shoulder mounts.

The TA-PV2J650 incorporates an integral IDX V-Mount plate allowing direct mounting of any IDX ENDURA battery. The TA-PV2J650 has a D-Tap connector that supplies 12-16.8V DC power from the battery allowing the use of professional on-board camera lights and other accessories.



Technical Specification:

Cable Output Voltage:
12V DC (regulated)

D-Tap Output Voltage:
12~17V DC (unregulated)

Max. D-Tap Output:
50W

Cable Length:
5.5ft / 1.7m approx.

Dimensions:

82.5(W) x 142(H) x 12(D) mm
3.24(W) x 5.59(H) x 0.47(D) inch

Weight:
0.46lbs. / 210g approx.

Included Accessories:
M3 x 8(mm) screw x 4

Camera Runtime Chart

GY-HM600/GY-HM650 with VF and LCD Monitor

E-7S	E-HL9/ E-HL9S	DUO-95	ELITE	DUO-150
5.6 hours	7.2 hours	7.7 hours	11.3 hours	12.1 hours

Note: Runtimes are approximate and are based on new batteries

Optional IDX Accessories



A-CP(A)



TA-CA2

IDX System Technology, Inc.
19001 Harborage Way, Suite 105
Torrance, Ca 90501
U.S.A.
Telephone: (310) 328-2850
Fax: (310) 328-8202



For further information email: idx.usa@idx.tv or visit our website www.idxtek.com
IDX reserves the right to change the specifications contained herein without notice.