

USB Bal Box

USB Balance Box eliminates hum problems when connecting audio from your presentation computer source. Hum can happen anywhere, you don't have to be running your audio signal a long distance. Power supplies, fluorescent lights and all sorts of equipment can cause noise that is picked up by your audio input cables.

The USB Bal box is a self-contained sound card therefore bypasses the internal DAC of the host machine providing a clean sound without pre-emphasis that can be used on headphone drives.



The USB 'Hum' Eliminator

Main Features

- ✓ True audio reproduction
- ✓ Improved bandwidth
- ✓ 600ohm line level driven output
- ✓ Earth (Ground) lift
- ✓ Left/Right XLR output connectors are standard
- √ for live events audio
- ✓ USB powered
- √ Compact size

3 Year Limited Factory Warranty

Specifications:

Signals:

Typical USB input

Bandwidth: 85Hz to 18KHz signal levels

Control Switches:

Earth (Ground) lift Stereo to Mono

Otoroo to mo

Connections:

USB input

Output: 2male XLR

Dimensions mm (inch):

DxWxH:71($2^{4}/_{5}$ ")x 64($2\frac{1}{2}$ ")x 40($1^{3}/_{5}$ ")

Supplied USB input cable

Weight:

218g / 8oz

Power:

USB powered

Interspace Industries

Unit 1A, 126 Great North Road, Hatfield, Hertfordshire AL9 5JN, UK

call: +44 (0) 1462 600 101 email: moreinfo@interspaceind.com web: www.interspaceind.com



