

56-in-1 Memory Card Reader/Writer

GFR281



- Easy installation; Plug-n-Play
- Reads and writes multiple media cards at one time
- **CompactFlash Type I, II**
- **High Capacity support:** SDHC/microSDHC
- SD/Mini SD/MMC/microSD/T-Flash, transfer your slotMusic™ songs to your PC or Mac
- **Olympus and Fuji Film flash memory**
- **Memory Stick/MS Duo**
- **Memory Stick Micro (M2)**
- Remarkable high-speed digital image and data transfer to computer
- USB 2.0 transfer speeds up to 480Mbps.

- No power adapter needed
- Works with all popular memory cards without additional adapters required
- Specifically designed for digital cameras and also ideal for using with Palmtop PCs, Handheld PCs, PDAs, Voice Recorders and other mobile electronics
- Hot swapping capacity for replacing PC storage cards without restarting the computer

Drive letter recognition software can be downloaded from "Driver & Manual" section. The software can replace confusing icons with memory card slot icons for easier access.

IOGEAR's newest Universal Memory Bank, 56-in-1 Memory Card Reader/Writer, is an ideal solution for hi-speed, bi-directional image and data file transfer between your computer and multimedia devices. Images and data can be downloaded directly from your memory cards*. It works with all major memory card formats and supports high capacity: CompactFlash/Micro Drive, SD/SDHC/Mini SD/MMC, Olympus and Fuji Film flash memory, T-Flash/microSD/ microSDHC, Memory Stick/MS Duo, Memory Stick Micro (M2). With direct USB 2.0 high-speed file transfer (up to 480Mbps) from memory cards used in your digital cameras, cellphone, or MP3 devices, you can save time and conserve power on devices. It also instantly transfers your slotMusic™ songs to your PC or Mac. No matter where you go, IOGEAR's Universal Memory Bank helps you to easily bring your digital images and data with you.

High Capacity Support
**SDHC/
microSDHC**

Supporting Media List:

- Compact Flash/Micro Drive: CF-Type I, CF-Type II, CF-Ultra II, Microdrive, CF-Pro II, CF-Extreme, CF-Extreme III, CF-PSP II, CF-Supper, CF-Ultra X
- SD/SDHC: SD, SDHC, SD-Pro, SD-Pleomax, SD-Pro C, Ultra II SD, Ultra II Plus SD, SD-Extreme III, SD-Ultra X, SD-Turbo, SD-Supper, SD Max, Mini SD, Mini SD-Pro, Mini SD-Pleomax, MMC, MMC-Pleomax, MMC Pro, HS-MMC, MMC Plus, MMC-Plus Turbo, RS MMC, RS MMC-Pleomax, RS MMC-Speed, RS MMC-Max, MMC Mobile, MMC Mobile-ProC, MMC Mobile-Pocketnet, MMC Micro*
- Olympus DC Card: Olympus DC Card, Olympus DC Card(M), Olympus DC Card (H)
- microSD/microSDHC: microSD/microSDHC, T-Flash
- Memory Stick: MS, MS-Magic Gate, MS-PRO Magic Gate, HS-MS-PRO Magic Gate, MS-DUO, MS DUO Magic Gate, MS-PRO Duo, HS-MS-PRO Duo, HS-MS-PRO Duo Magic Gate, MS-PRO Duo-PSP, MS-PRO Duo-Gaming Memory Stick
- M2: Memory Stick Micro (M2)

* Adapter required.

** Supply of this implementation of TPL's CORE Flash technology does not convey a license nor imply a right under any patent, or any other industrial or intellectual property right of TPL, to use this implementation in any finished end-user or ready-to-use final product. You are hereby notified that a license for such use is required from TPL. Contact: "coreflash@alliacense.com"




56-in-1 Memory Card Reader/Writer

How does it work?

Transfers files, images, and music between your computer and digital camera, cell phone, smartphone, or PDA at speeds of up to 480 Mbps.

Reads and writes all popular memory cards with no adapters required.



Product Requirements

For PC users:


- Windows XP*, Windows Vista, Windows 7, and Windows 8/8.1
- Available USB port (USB 2.0 port for Hi-Speed mode)

For MAC users:

- Mac OS 10.1.2 ~ 10.10.3
- Available USB port (USB 2.0 port for Hi-Speed mode)

Package Contents

- 1 x 56-in-1 Card Reader/Writer
- 1 x USB Cable (Type A - mini B)
- 1 x Quick Start Guide

* Windows XP® systems require  [Microsoft Windows](http://www.microsoft.com) to support SDXC cards

Specifications

Function	GFR281	Dimensions	GFR281
Housing		POP Information	
Case	Plastic	10" Peg Hook	5
Ports	(1) USB mini-B port	6" Peg Hook	3
Operating Temperature	- 40 ~ + 176 F (- 40 ~ + 80 C)	Unit Dimensions	
Storage Temperature	+ 32 ~ + 158 F (0 ~ + 70 C)	Height	0.625 in.
Operating System Support	Win 2000, XP, Vista, MAC 10.2.1 or greater	Depth	2.3 in.
USB Specification	USB 1.1 and 2.0 compliant	Length	4 in.
Transfer Rate	480 Mbps	Inner Pack	
Humidity	20-80% RH, (Non Condensing)	Width	6.75 in.
Cable Type	1 - USB 2.0 Cable (Type mini-B to A) 3-feet	Height	7.5 in.
Power Mode	Bus Powered	Depth	10 in.
		Inner Pack Qty.	6
		Unit Package Dimensions	
		Width	2.25 in.
		Height	10.25 in.
		Length	6.75 in.
		Master Carton	
		Width	10 in.
		Height	14 in.
		Depth	15.5 in.
		Master Carton Qty.	24
		Weight	
		Master Carton Wt.	11 lb.
		Inner Pack Wt.	2.6 lb.
		Unit Pack Wt.	0.5 lb.
		Unit Wt. w/accessories	0.28 lb.
		Unit Wt.	0.25 lb.

GFR281