

Interloop™

Wired-Wireless Intercom Beltpack



FEATURES

- » HD Voice (Wide-Band Speech)
- » Bluetooth Wireless Technology
- » 2.4 GHz Encrypted Digital Wireless
- » 3-pin XLR Male and Female Intercom Jacks
- » Send and Receive Volume Controls
- » PTT Button
- » Connects to Bluetooth Headsets, Phones, & Notebooks
- » Intercom Powered with 9 Volt Battery Backup

Stay in the Loop.

Interloop™ works with industry standard Two-Wire, Party-Line intercoms, connecting to the existing intercom system like any other belt pack. Utilizing Bluetooth Wireless Technology, a rear panel switch selects Headset or Phone connection. Headset mode allows you to connect to a Bluetooth enabled headset for wireless freedom. Phone mode allows you to connect to a wireless phone to let others join in, or connect to a notebook or laptop to provide remote voice access using VoIP applications such as Skype™.

Battery Backup. Powered by the intercom system, yet uses less current than a typical belt pack. Includes 9 VDC battery backup, holding the wireless connection while changing cables.

Increased Range. While Interloop™ will work with any Bluetooth enabled headset, most headsets were designed to work a short distance from the phone. JK Audio BSET-HS1 Wireless Headset offers increased range and performance making it the perfect match.

HD Voice. While standard phone calls have a narrow bandwidth of 300 Hz to 3.4 kHz, HD Voice calls offer 50 Hz to 7 kHz bandwidth. The additional 1.5 octaves on the low end gives voice a more natural sound, while the additional upper octave dramatically improves speech clarity and intelligibility.

**7 kHz
HD VOICE**

Wireless HD Calls. To take advantage of this extended bandwidth, both phones on the call must support HD Voice, and both phones must be on the same carrier, in coverage areas that support HD Voice.

Interloop™

Wired-Wireless Intercom Beltpack

REAR VIEW



SPECIFICATIONS

XLR Intercom Channel

| | |
|-------------------------------|-------------------------------|
| Output Level: | 0 dBu (775 mV) nominal |
| Terminating Impedance: | 200 ohms |
| Bridging Impedance: | >15k ohms |
| Pin 1: | Common |
| Pin 2: | +30 VDC (+12 VDC min) 35 mA |
| Pin 3: | Audio |

Bluetooth Wireless Technology

| | |
|----------------------------|--|
| Standard: | Bluetooth 3.0 |
| Profile: | Hands Free (HF) |
| Distance: | 40 feet (12 meters) |
| Frequency Response: | 300 Hz -3.4 kHz 50 Hz - 7 kHz with HD Voice |
| Power: | Intercom System with 9 VDC Battery backup |
| Size: | 4.7" x 3.75" x 1.65" (12 x 9.5 x 4.2 cm)) |
| Weight: | 10 ounces (275 grams) |



The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by JK Audio, Inc. is under license.