

## The new standard in **HDMI** matrix technology

The Just Add Power 2G Rackmount 3-in-1 Transmitter is the source-side encoding device in the HD over IP matrix system.

- Connect to source via HDMI
- Connect to network via Ethernet
- Instant-seamless switching
- 2-way RS232 Control

Features
Stereo or multi-channel audio
Instant-seamless Switching
Video Wall
Image Pull
2-way RS232 control
Image Push

**Not your ordinary matrix!** Don't settle for simple matrix control when you can have all of these features built-in. 2G Rackmount 3-in-1 Transmitters are fully compatible with all 2G+ and 2G+AVP models.

## 2G Rackmount 3-in-1 Transmitter



Compliancy	HDCP & RoHS/FCC/CE
Operating Temp	0-60 °C / 32-140 °F
Supported	Up to 1080p50/60 Hz
Resolutions	PC: 1920 x 1200
	429 x 44.5 x 250 mm
<b>Dimensions &amp;</b>	17" x 1.75" x 9.8"
Weight	(19-inch rack, 1 RU)
	2.9 kg / 6.4 lb
	HDMI In (x3)
Ports	Ethernet connector (x3)
	RS232 (Female DB9) (x3)
Bandwidth	Up to 150 Mbps
Dawas Cumply	Standard Power Cable
Power Supply	IEC 60320 C13/C14
(included)	30 watts maximum





