

3G SDI 1x8 Splitter

Distribute 1 SDI Signal to 8 SDI Monitors

MPN: SP-SDIX8



The KanexPro 1x8 SDI unit can split, re-clock, and amplify SDI source video to 8 SDI outputs providing full HD 1080p resolution to up to 8 displays simultaneously for faster broadcasting and production.

The splitter accepts one SDI input from the SD-SDI, HD-SDI, or 3G-SDI video source such as VTR, SDI recorders and other sources. After replicating the signal perfectly, it automatically deploys cable equalization to simultaneously transmit SDI signals as far as 1000 feet (300 m) over 8 x BNC coax runs to 8 monitors. For HD-SDI video, the splitter goes up to 500 feet (150 m) and for 3G-SDI video, up to 328 feet (100 m).

Ideally used with SDI based surveillance systems, rental & staging facilities, post-production, TV studio, digital cinema, or other A/V applications where you need to split and extend from a camera or other device equipped with 3G/HD/SD-SDI outputs to 8 SDI-compliant displays or video processors.

FEATURES

- Get the highest quality 3G SDI distribution to 8 SDI monitors
- Outputs video on 8 separate buffered and re-clocked BNC ports.
- Built-in equalizer for I/O drive at long distances over RG6
- Supports multiple video resolutions:
 - SDI 525i, 625i
 - HD: 720p 24, 25, 30, 50 & 60 Hz.
 - HD: 1080i 50 & 60 Hz.
 - HD: 1080p 24, 25, 30, 50 & 60 Hz.
- 3G: 1080p 50/60Hz.
- Compatible with HDCctv 1.0, HD-SDI (ST 292), 3G-SDI (ST 424) and SD-SDI (ST 259)
- Supports Multiple Color Space: RGB or YCbCr 4:4:4 sampling
- Support for YCbCr: 4:2:2 sampling
- Data rates up to 2.97 Gbps
- Color Depth Support: 8 bit, 10 bit & 12 bit
- LED's for power and input signal
- Automatically switches between SD, HD and 3 Gb/s SDI standards
- Rack sized metal enclosure

SPECIFICATIONS

Video Input


- Input: 1xSDI Male
- Input Connector: 1xBNC Male
- Input Video Signal: SD/HD/3G SDI

Video Output

- Output: 16 x SDI Male
- Output Connector: 16xBNCs
- Output Video Signal: SD/HD/3G SDI

Resolutions (HDTV)

- 1080p, 1920x1080
- 720p; 1280x720
- 1280x720, 480i (NTSC mode) 576i Standard PAL mode



ABOUT KANEXPRO

KanexPro carries a broad selection of A/V connectivity products by leveraging the core strength in professional systems enabling you to broadcast, convert, extend, split, or multiply HD signal transmissions; simply and cost-effectively. KanexPro is a trademark. HDMI, the HDMI logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing, LLC in the United States and/or other countries. All other product or service names are the property of their respective owners.