

101L

1:1 Composite Video Line Amplifier





The 101L is a high-performance line amplifier for composite video signals. It provides controls to compensate for signal loss inherent in long cable runs.

FEATURES

- Bandwidth 500MHz (-3dB).
- Controls Level (gain) & EQ (peaking) on recessed trimmers to prevent unintentional resetting.
- Compact MultiTOOLS® 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-1 universal rack adapter.

101L

TECHNICAL SPECIFICATIONS

INPUT: 1 composite video, $1Vpp/75\Omega$ on a BNC connector. OUTPUT: 1 composite video, $1Vpp/75\Omega$ on a BNC connector.

MAX. OUTPUT LEVEL: 2.5Vpp.
BANDWIDTH: 500MHz.
DIFF. GAIN: 0.03%.
DIFF. PHASE: 0.03Deg.
S/N RATIO: 75dB.

CONTROLS: Level: -0.8dB to 6.5dB; EQ.: 0dB to 8dB.

COUPLING: DC.

POWER CONSUMPTION: 12V DC, 60mA.

DIMENSIONS: 5.32cm x 4.36cm x 7.25cm (2.09" x 1.72" x 2.85") W, D, H.

WEIGHT: 0.15kg (0.33lbs) approx.

INCLUDED ACCESSORIES: Power supply.

OPTIONS: RK-1 19" rack adapter.

