



104LN

1:4 Composite Video Differential Line Amplifier



The **104LN** is a high-performance line amplifier for composite or SDI video signals. It includes differential circuitry to help eliminate noise often found on the input cable in a long run.

FEATURES

- High Bandwidth - 423MHz (-3dB).
- Differential Circuitry - Reduces noise & hum found in long cable runs.
- Level (Gain) and EQ (Peaking) Controls.
- Compact Kramer TOOLST™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



104LN

TECHNICAL SPECIFICATIONS

INPUT:	1 composite/SDI video, differential, 1Vpp/75Ω on a BNC connector.
OUTPUTS:	4 composite/SDI video, 1Vpp/75Ω on BNC connectors.
MAX. OUTPUT LEVEL:	1.6Vpp.
BANDWIDTH (-3dB):	423MHz.
DIFF. GAIN:	0.22%.
DIFF. PHASE:	0.1Deg.
K-FACTOR:	<0.05%.
S/N RATIO:	73.3dB.
CONTROL:	Level: -1.3 to 6dB; EQ. 0 to 10.2dB.
COUPLING:	DC.
POWER CONSUMPTION:	12V DC, 95mA.
DIMENSIONS:	12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98"), W, D, H.
WEIGHT:	0.3kg (0.66lbs) approx.
INCLUDED ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.

