



## FC-332

### 3G HD-SDI to HDMI Format Converter

---



The **FC-332** is a high-performance format converter for video signals up to 3G HD-SDI. The unit converts the input video format (with embedded audio) to two HDMI outputs.

### FEATURES

---

- HDTV Compatible.
- Looping Input.
- Multi-Standard Operation - SDI (SMPTE 259M), HD-SDI (SMPTE 292M) and 3G HD-SDI (SMPTE 424M) compliance and support for data rates of 270Mbps, 1483.5Mbps, 1485Mbps and 2970Mbps.
- Embedded Audio Group Select Rotary Switch.
- Active Input Indication™ Reporting - Green indicates a standard definition (SDI) input signal and blue indicates a high definition (HD-SDI) input signal.
- Compact DigiTOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



## FC-332

### TECHNICAL SPECIFICATIONS

INPUT: 1 SD/HD/3G HD-SDI with loop on BNC connectors.  
OUTPUTS: 2 HDMI connectors.  
MAX. DATA RATE: Up to 3Gbps.  
STANDARD COMPLIANCE: HDMI.  
INDICATOR LEDS: SD/HD, OUT, ON.  
POWER CONSUMPTION: 5V DC, 510mA.  
DIMENSIONS: 12cm x 7.2cm x 2.4cm (4.7" x 2.8" x 1.0") W, D, H.  
WEIGHT: 0.3kg (0.7lbs).  
INCLUDED ACCESSORIES: Power supply.  
OPTIONS: RK-3T 19" rack adapter.

