



KDS-EN3

H.264 Encoder, Recorder & Streamer



The Kramer **KDS-EN3** is an H.264 encoder for HDMI signals up to 1080p60. The **KDS-EN3** provides unicast (one-to-one) or multicast (one-to-many) streaming to the KDS-DEC3 decoder or computers running VLC© software. **KDS-EN3** can also record content to a network drive for later access.

FEATURES

- AVC Support - MPEG-4 using H.264 & AAC codecs.
- Built-in Scaling and Frame Rate Control - For lower bandwidth consumption when distributing over the network.
- Open Encoding - Enable software decoding through VLC© player software.
- Standard Ethernet Network Operation - 10/100/1000Mb.
- Video Support - HDMI.
- Audio Support - HDMI or analog.
- Streaming Support - Unicast and multicast through RTSP (Real Time Streaming Protocol).
- KDS-EN3 Manager Software - Allows remote management of the KDS-EN3 network including auto-detection and discovery of KDS-EN3/KDS-DEC3 units on a subnet.
- Manual & Scheduled Recording - To network storage option on encoders.
- RS-232 Virtualization - From encoder to decoder.



KDS-EN3

TECHNICAL SPECIFICATIONS

INPUTS:	1 HDMI, 1 unbalanced stereo audio on a 3.5mm mini jack (line in).
OUTPUTS:	1 HDMI, 1 VGA on a 15-pin HD connector, 1 unbalanced stereo audio on a 3.5mm mini jack.
PORTS:	1 Ethernet on an RJ-45 connector, 1 RS-232 on a 9-pin D-sub connector.
VIDEO SINGLE CHANNEL HD:	Up to 1920x1080p60 and 1920x1200(60Hz).
COMPRESSION STANDARD:	H.264/Mpeg4 Part 10 (AVC).
PROFILES:	Baseline, Main, High.
LEVELS:	Up to 4.2.
BIT RATES:	100Kbps to 25Mbps.
RATE CONTROL:	CBR, VBR, adjustable GOP (Group Of Pictures) size.
AUDIO COMPRESSION STANDARD:	MPEG4 AAC-LC.
CHANNELS:	2 channel (stereo), HDMI with digital L-PCM audio.
ANALOG SAMPLE FREQUENCY:	32, 44.1, and 48kHz.
BIT RATES:	96, 128, 192, and 256Kbps.
INPUT RESOLUTIONS:	1920 × 1200, 1920 × 1080, 1680 × 1050, 1600 × 1200, 1600 × 900, 1440 × 900, 1400 × 1050, 1360 × 768, 1280 × 1024, 1280 × 960, 1280 × 720, 1024 × 768, 800 × 600, 720 × 576, 720 × 480, and 640 × 480.
OUTPUT RESOLUTIONS:	1600 × 900, 1440 × 900, 1400 × 1050, 1366 × 768, 1360 × 768, 1280 × 1024.
MAXIMUM UNICAST CONNECTIONS:	8.
POWER CONSUMPTION:	5V DC, 3A max.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	21.6cm × 2.6cm × 10.7cm (8.5" × 1.0" × 4.0").
WEIGHT:	0.36kg (0.26kg).
INCLUDED ACCESSORIES:	Power supply, power cord, plastic bracket set.