



TR-2A

Balanced Stereo Audio Isolation Transformer



The **TR-2A** is a high-performance isolation transformer for balanced stereo audio signals. It completely isolates devices to eliminate hum, ground loops, and DC offsets that can degrade audio quality.

FEATURES

- S/N Ratio - -83dB @+4dBu, 1kHz.
- External Input & Output Ground Terminals.
- Grounding Options - DIP-switch selectable.
- Passive - No power required.
- Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3TR rack adapter.



TR-2A

TECHNICAL SPECIFICATIONS

INPUT:	1 balanced stereo audio, +4dBu/600Ω on detachable terminal block.
OUTPUT:	1 balanced stereo audio, +4dBu/600Ω on detachable terminal block.
MAX. OUTPUT LEVEL:	+26dBu.
BANDWIDTH (-3dB):	20Hz to 20kHz.
S/N RATIO:	-83dBu @+4dBu/1000Hz.
CONTROLS:	DIP-switches to connect to chassis.
COUPLING:	Transformer.
AUDIO THD + NOISE:	0.025% @+4dBu/1000Hz.
DIMENSIONS:	12.1cm x 7.2cm x 3cm (4.77" x 2.85" x 1.2") W, D, H.
WEIGHT:	0.34kg (0.75lbs) approx.
INCLUDED ACCESSORIES:	Mounting brackets.
OPTIONS:	RK-3TR 19" rack adapter.

