



## VM-24H

### 2x1:4 HDMI Distribution Amplifier

---



The **VM-24H** is a distribution amplifier for HDMI signals. The unit reclocks and equalizes one of two selectable input signals and distributes it to four identical outputs.

## FEATURES

---

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliant.
- HDMI Support - Deep Color, x.v.Color™, Lip Sync, CEC.
- 3D Pass-Through.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- Active Output LED Indicators.
- Control - Front panel, RS-232, IR switching.
- Worldwide Power Supply - 100-240V AC.
- Standard 19" Rack Mount Size - 1U. Rack "ears" included.



## VM-24H

### TECHNICAL SPECIFICATIONS

|                                |   |
|--------------------------------|---|
| INPUTS:                        | 2 HDMI connectors.  |
| OUTPUTS:                       | 4 HDMI connectors.  |
| BANDWIDTH:                     | 6.75Gbps (2.25Gbps per graphic channel).  |
| COMPLIANCE WITH HDMI STANDARD: | Supports HDMI and HDCP.   |
| CONTROLS:                      | EDID SELECT, EDID READ, IN 1, IN 2 buttons, RS-232, IR.                             |
| INDICATOR LEDs:                | Output status LEDs.   |
| POWER CONSUMPTION:             | 100–240V AC, 50/60Hz, 16VA.   |
| DIMENSIONS:                    | 19" x 7" x 1U W, D, H, rack mountable.  |
| WEIGHT:                        | 2.5kg (5.5lbs) approx.  |
| INCLUDED ACCESSORIES:          | Power cord, null-modem adapter, Windows®-based control software, IR remote control. |
| OPTIONS:                       | External remote IR receiver cable.  |

