



VP-200xIn

1:2 Computer Graphics Video Line & Distribution Amplifier



Compatible with HDTV component video signals when used with a breakout cable such as the Kramer C-GM/3RVF.



The **VP-200xIn** is a high-performance line and distribution amplifier for computer graphics video signals with resolutions up to and exceeding UXGA. It provides controls to compensate for signal losses inherent in long cable runs.

FEATURES

- High Bandwidth - 400MHz (-3dB).
- HDTV Compatible.
- Level (Gain) and EQ (Peaking) Controls.
- ID Bit Control.
- AC/DC Coupling Selection - Individually for R, G, & B signals.



VP-200xIn

TECHNICAL SPECIFICATIONS

INPUT:	1 UXGA on a 15-pin HD (F) connector.
OUTPUTS:	2 UXGA on 15-pin HD (F) connectors.
MAX. OUTPUT LEVEL:	2Vpp.
BANDWIDTH (-3dB):	400MHz.
DIFF. GAIN:	0.05%.
DIFF. PHASE:	0.03Deg.
K-FACTOR:	<0.05%.
S/N RATIO:	71dB.
CONTROLS:	Level: -1.5dB to +6.1dB, EQ.: 0 to +7.3dB @50MHz.
COUPLING:	AC/DC.
POWER CONSUMPTION:	12V DC, 95mA.
DIMENSIONS:	12cm x 7.15cm x 2.76cm (4.7" x 2.8" x 1.08") W, D, H.
WEIGHT:	0.3kg (0.66lbs) approx.
INCLUDED ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.

