



VP-506

DVI & Computer Graphics Video Scan Converter



Compatible with HDTV component video signals when used with a breakout cable such as the Kramer C-GM/3RWF.



The **VP-506** is a high-quality scan converter for down-scaling DVI, computer graphics (VGA) and component video (YPbPr) to PAL or NTSC video. It supports VGA up to UXGA, as well as component resolutions up to 1080p.

FEATURES

- Max. Resolution - UXGA & 1080p.
- HDTV Compatible Input.
- Selectable Video Standards - PAL or NTSC.
- Memory Locations - Saves and recalls up to four setups, including picture, input, output, zoom and advanced feature setups.
- Built-In ProcAmp Features - Color, sharpness, contrast and brightness.
- Control - Front panel buttons and OSD (on screen display).
- Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



VP-506

TECHNICAL SPECIFICATIONS

INPUT:	1 DVI-I (DVI-D, VGA, YPbPr) on a 24-pin Molex connector.
OUTPUT:	1 composite video, 1Vpp/75Ω on an RCA connector.
INPUT RESOLUTIONS:	Up to WUXGA/1080p.
CONTROLS:	Front panel and OSD: ProcAmp video controls, freeze, underscan/overscan, 8 color bars.
POWER CONSUMPTION:	5V DC, 540mA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98") W, D, H.
WEIGHT:	0.3kg (0.67lbs) approx.
INCLUDED ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.

