



VP-6xIn

1:6 Computer Graphics Video Distribution Amplifier



Compatible with HDTV component video signals when used with a breakout cable such as the Kramer C-GM/3RVF.



The **VP-6xIn** is a high-performance distribution amplifier for computer graphics video signals with resolutions up to and exceeding UXGA. It takes one input, provides correct buffering and isolation, and distributes the signal to six identical outputs.

FEATURES

- High Bandwidth - 500MHz (-3dB).
- HDTV Compatible.
- ID Bit Control.
- EQ (peaking) Control.
- Standard 19" Rack Mount Size - 1U. Rack "ears" included.



VP-6xIn

TECHNICAL SPECIFICATIONS

INPUT:	1 UXGA on a 15-pin HD (F) connector.
OUTPUTS:	6 UXGA on 15-pin HD (F) connectors.
MAX. OUTPUT LEVEL:	1.7Vpp.
BANDWIDTH:	500MHz.
DIFF. GAIN:	0.09%.
DIFF. PHASE:	0.01Deg.
K-FACTOR:	<0.05%.
S/N RATIO:	72dB.
CONTROLS:	0 to +10dB EQ.
COUPLING:	DC.
POWER CONSUMPTION:	100-240V AC, 50/60Hz, 18VA.
DIMENSIONS:	19" x 7" x 1U W, D, H, rack mountable.
WEIGHT:	2.7kg (6lbs) approx.
INCLUDED ACCESSORIES:	Power cord, rack "ears".

