

VP-701xI

Computer Graphics Video & HDTV Scan Converter









Compatible with HDTV component video signals when used with a breakout cable such as the Kramer C-GM/3RVF.



The VP-701xl is a scan converter for computer graphics video signals. The unit converts computer graphics video signals up to 2048x2048 or HDTV signals up to 1080p to two composite and two s-Video (Y/C) signals simultaneously in either PAL or NTSC formats.

FEATURES

- Input Compatibility Up to 2048x2048 and 1080p.
- HDTV Compatible.
- AutoTrak™ Auto Setup Technology One button auto setup that automatically sizes, shifts, and centers any input image on the display device.
- Multi-Standard Output PAL or NTSC (selectable).
- Looping Input.
- Built-In ProcAmp Brightness, contrast, color, hue (NTSC only).
- Flicker Reduction 2, 4 or 6-line flicker reduction (selectable).
- Freeze Frame.
- Front Panel Lock Out.
- Aspect Ratio 3 settings.
- Zoom & Pan Up to 10x.
- Control RS-232 (for firmware updates) & IR remote (included) with on-screen display.
- Power Supply 12V DC.
- Desktop Size Compact size. Can be rack mounted in a 1U rack space with the optional RK-701xl adapter.

VP-701xI

TECHNICAL SPECIFICATIONS

INPUT: 1 computer graphics or component HDTV with loop on 15-pin HD connectors.

OUTPUTS: 2 CV on BNC connectors, 2 s-Video on 4-pin connectors.

INPUT RESOLUTION: Up to 2048x2048 (computer) and 1080p (HDTV). 24-100kHz H-Freq & 40-150Hz V-Freq.

OUTPUT STANDARDS: NTSC or PAL (selectable).

CONTROLS: Front panel, IR, and RS-232.

POWER CONSUMPTION: 12V DC.

DIMENSIONS: 21.85cm x 15.0cm x 4.2cm (8.6" x 5.9" x 1.65") W, D, H.

WEIGHT: 0.6kg (1.3lbs) approx.

INCLUDED ACCESSORIES: Power supply.

OPTIONS: RK-701xl 19" rack adapter.

