



VP-747T

In-CTRL™ Remote Control Console with T-Bar



The **VP-747T** is a dedicated remote control console for the VP-747 In-CTRL dual scaler seamless switcher. It is designed for use at live production events that require remote operation of the seamless switcher from a T-bar for precise switching and transition control.

FEATURES

- **All VP-747 Functions Replicated** - All the front panel controls of the VP-747 Seamless Switcher are replicated on the VP-747T.
- **Convenient Switching Control** - Via T-bar or Take button with selectable transition speed control.
- **Menu Button** - Control the VP-747 via an on-screen display on the preview output.
- **Wipe Direction Control** - Via front panel buttons.
- **Control Multiple Units** - Up to 4 VP-747 Seamless Switchers can be controlled from one VP-747T.
- **Gooseneck Lamp** - For low light environments.
- **Control Options** - 4 RS-485 ports (2 mini-XLR & 2 terminal block) to control up to 4 VP-747 units, and 1 RS-232 for firmware upgrades.
- **Power Supply** - 12V DC.
- **Note** - Angled faceplate allows for free-standing use on a table.



VP-747T

TECHNICAL SPECIFICATIONS

PORTS:	2 sets of RS-485 on 3-pin terminal block connectors, 2 sets of RS-485 on mini-XLR connectors.
CONTROLS:	Front panel buttons, RS-232, and RS-485.
POWER CONSUMPTION:	12V DC, 280mA.
DIMENSIONS:	19" x 7" x 4U W, D, H, rack mountable.
WEIGHT:	1.58kg (3.5lbs) approx.
ACCESSORIES:	Gooseneck lamp, 2 mini XLR connectors, power supply, rack "ears", table top brackets.

