



VS-211HDxI

2x1:2 3G HD-SDI Automatic Standby Switcher



The **VS-211HDxI** is a high-performance automatic switcher for 3G HD-SDI video signals. When configured as a standby switcher, it switches to the secondary input when the primary input is lost.

FEATURES

- Max. Data Rate - 3Gbps.
- Multi-Standard Operation - SDI (SMPTE 259M and SMPTE 344M), HD-SDI (SMPTE 292M) & 3G HD-SDI (SMPTE 424M).
- HDTV Compatible.
- Control - Contact closure or automatic switching.
- Automatic Standby Switching - Switches from the secondary input to the primary input when a primary signal is detected.
- Primary Input - Selectable.
- Active Input LED Indicators.
- Compact DigiTOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



VS-211HDxI

TECHNICAL SPECIFICATIONS

INPUTS:	2 SD/HD/3G HD-SDI video on BNC connectors.
OUTPUTS:	2 SD/HD/3G HD-SDI video on BNC connectors.
MAX. OUTPUT LEVEL:	800mVpp/75Ω.
DATA RATE:	Up to 2.97Gbps.
CONTROLS:	Contact closure remote control, input default selection switch.
COUPLING:	AC.
POWER CONSUMPTION:	5V DC, 400mA.
DIMENSIONS:	12cm x 7.2cm x 2.4cm (4.7" x 2.8" x 1.0") W, D, H.
WEIGHT:	0.3kg (0.66lbs).
INCLUDED ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.

