



## VS-21H-IR

2x1 HDMI Switcher with IR



The **VS-21H-IR** is a high-performance switcher for HDMI signals. It reclocks, equalizes and switches either of two inputs to a single HDMI output.

### FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDTV Compatible.
- HDCP & HDMI Compliant.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.
- EDID PassThru - Passes EDID signals between the source and display.
- HDMI Support - Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD, CEC.
- Active Input & Output LED Indicators.
- Control - Front panel or IR remote controller (included).
- Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



## VS-21H-IR

### TECHNICAL SPECIFICATIONS

INPUTS:	2 HDMI connectors.
OUTPUT:	1 HDMI connector.
BANDWIDTH:	6.75Gbps (2.25Gbps per graphic channel).
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
CONTROLS:	Input select button, IR remote control.
INDICATOR LEDs:	IN 1, IN 2, OUT, and ON LEDs.
POWER CONSUMPTION:	12V DC, 180mA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	12cm x 7.15cm x 2.76cm (4.7" x 2.8" x 1.08"), W, D, H.
WEIGHT:	0.3kg (0.66lbs) approx.
INCLUDED ACCESSORIES:	Power supply, bracket installation kit, IR transmitter.
OPTIONS:	RK-3T 19" rack adapter.

