



VS-4228

8-Port RS-422 Matrix Switcher



The **VS-4228** is a high-performance bidirectional matrix switcher for RS-422 control signals. It can connect multiple ports to create from one to four bidirectional communication groups.

FEATURES

- **Control** - Front panel, RS-232 (K-Router Windows®-based software is included & RS-485.
- **Memory Locations** - Stores multiple switches as presets for recall and execution when needed.
- **Front Panel Control Lockout.**



VS-4228

TECHNICAL SPECIFICATIONS

INPUT/OUTPUT:	8 in/out ports on 9-pin D-sub (F) connectors.
CONTROL:	Front panel buttons, RS-485 and RS-232 serial interface (in and out).
INDICATORS:	8-character display on the front panel.
STANDARDS COMPLIANCE:	TIA/EIA-422-B and SMPTE 207M.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	19" x 7" x 1U (W, D, H) rack-mountable.
POWER CONSUMPTION:	230V AC, 50/60 Hz, (115V AC, U.S.A.) 10VA.
WEIGHT:	2.2 kg (4.88 lbs) approx.
INCLUDED ACCESSORIES:	Power cord, Windows® Control Software.

